

AXIS TQ1943-E Cable Gland Ex d Armored

Cable gland for armored cables

For hazardous area compliance, the Ex d cable gland maintains a secure entry where the armored cable connects to the camera or junction box. The cable gland is certified for flameproof enclosures. It comes in two sizes to fit cable entries with M20x1.5 or M25x1.5 threads. It has an IP66/IP67 and 68-rating which means it is protected from dust and water ingress and designed for harsh weather conditions.

- > Certified for ATEX, IECEx, INMETRO, PESO and IA
- > M20 or M25
- > Deluge protected
- > IP66-, IP67- and IP68-rated



www.cxis.com T10204195/EN/M3.2/2407

AXIS TQ1943-E Cable Gland Ex d Armored

Approvals Product marking Supply chain Environment	AXIS TQ1943-E Cable Gland Ex d Armored M20 AXIS TQ1943-E Cable Gland Ex d Armored M25 gs ATEX, CE, IECEx, UL, CCC, UKEX TAA compliant UL 50 NEMA 250 Type 4X Deluge protection compliance: DTS01: 91		Ex db IIC Gb Ex eb IIC Gb Certificate: P444949 IA: Ex db IIC Gb Ex eb IIC Gb Ex nR IIC Gc Ex ta IIIC Da Ex db I Mb Ex eb I Mb
Explosion	IEC/EN 60079-0, IEC/EN 60079-1, IEC/EN 60079-7, IEC/EN 60079-31, UL 60079-0, UL 60079-1, UL 60079-7, ANSI/UL 514B, 2225	General Casing	Certificate: MS-XPL21804 21.0011X IP66-, IP67-, IP68- and IK10-rated
Certifications	Model key: Triton T3CDS ATEX: Il 2G 1D Ex db IIC Gb Ex eb IIC Gb Ex et IIIC Da I M2 Ex db I Mb Ex eb I Mb Certificate: CML18ATEX1326X, CML18ATEX4318X IECEx: Ex db I Mb Ex eb I Mb Ex eb I Mb Ex eb IIC Gb Ex eb IIC Gb Ex et IIC Da Certificate: IECEx CML 18.0183X INMETRO: Ex db IIC Gb Ex eb IIC Gb Ex et IIC Gb Ex et IIC Gb Ex db IIC Gb Ex db IIC Gb Ex eb IIC Gc Ex ta IIIC Da Ex db I Mb Ex eb I Mb Certificate: TÜV 11.0374X PESO:		Nickel plated brass
		Operating conditions	-60 °C to 130 °C (-76 °F to 266 °F)
		Dimensions	Cable diameter M20: 12.5–20.9 mm M25: 14.0-22.0 mm
		Weight	M20: 0.28 kg (0.62 lb) M25: 0.44 kg (0.97 lb)
		Box content	Cable gland, sealing washer
		Warranty	5-year warranty, see axis.com/warranty
		Sustainability	
		Substance control	PVC free, BFR/CFR free in accordance with JEDEC/ECA Standard JS709 RoHS in accordance with EU RoHS Directive 2011/65/EU and 2015/863 and EN IEC 63000:2018 REACH in accordance with (EC) No 1907/2006. For SCIP UUID, see echa.europa.eu
		Environmental responsibility	axis.com/environmental-responsibility Axis Communications is a signatory of the UN Global Compact, read more at unglobalcompact.org

