

AXIS C1410 Network Mini Speaker

Speaker with wide-area coverage for voice messages

AXIS C1410 Network Mini Speaker is a discrete and affordable speaker that fits into smaller spaces and provides wide-area audio coverage. It allows users to remotely warn off intruders before they commit a crime, to deliver instructions during an emergency or to make general announcements. Built-in memory supports pre-recorded messages, or personnel can respond to notifications with live speak. Digital signal processing (DSP) ensures clear sound. Open standards support easy integration with network video, access control, analytics, and VoIP. AXIS C1410 is a standalone unit that can be placed almost anywhere, which supports a flexible, scalable and cost-effective approach to system design.

- > [All-in-one speaker system](#)
- > [Connects to standard network](#)
- > [Simple installation with PoE](#)
- > [Remote health testing](#)
- > [PIR sensor for motion detection](#)



AXIS C1410 Network Mini Speaker

Audio hardware		Supported codecs: PCMU, PCMA, opus, L16/16000, L16/8000, speex/8000, speex/16000, G.726-32	
Enclosure	One way enclosure with 2.5 inches broadband dynamic cone speaker	Intelligent audio Auto Speaker Test (verification via built-in microphone)	
Max sound pressure level	90 dB	Event triggers Virtual inputs, AXIS Camera Application Platform (ACAP) Call: DTMF, State changes	
Frequency response	100 Hz - 20 kHz	Event actions Play audio clip, send SNMP trap, send Auto Speaker Test, status LED, File upload via HTTP, network share and email, Notification via email, HTTP, HTTPS and TCP	
Coverage pattern	145° coaxial	Built-in installation aids Test tone verification and identification	
Audio input/output	Built-in microphone (can be disabled)	Cybersecurity	
Built-in microphone specification	50 Hz - 12 kHz	Edge security Software: Signed OS, brute force delay protection, digest authentication and OAuth 2.0 RFC6749 OpenID Authorization Code Flow for centralized ADFS account management, password protection	
Amplifier description	Built-in 7 W Class D amplifier	Network security IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2), HTTPS/HSTS, TLS v1.2/v1.3, Network Time Security (NTS), X.509 Certificate PKI, host-based firewall	
Digital signal processing	Built-in and pre-configured	Documentation <i>AXIS OS Hardening Guide</i> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> AXIS OS Software Bill of Material (SBOM) To download documents, go to axis.com/support/cybersecurity/resources To read more about Axis cybersecurity support, go to axis.com/cybersecurity	
Audio management		General	
AXIS Audio Manager Edge	Built in: – Content management for music and live/pre-recorded announcements. – Scheduling to decide when and where to play specific content. – Content prioritization to ensure urgent messages interrupt the schedule. – Zone management allowing you to divide up to 200 speakers into 20 zones. – Health monitoring for remote discovery of system errors. – User management to control who has access to what features. See separate datasheet for more details.	Casing Plastic casing, IP40 rated Colors: White Repaintable. For repainting instructions and impact on warranty, contact your Axis partner.	
AXIS Audio Manager Pro	For larger and more advanced systems. Sold separately. See separate datasheet for specifications.	Power Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 (max 12.95 W)	
AXIS Audio Manager Center	AXIS Audio Manager Center is a cloud service for remote access and management of multi-site systems.	Connectors RJ45 10BASE-T/100BASE-TX PoE	
Audio software		Reliability Designed for 24/7 operation.	
Audio streaming	One-way/two-way with optional half-duplex echo cancellation. Mono.	LED indicators Status LED, front-facing LED	
Audio encoding	AAC LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Axis μ -law 16 kHz, WAV, MP3 in mono/stereo from 64 kbps to 320 kbps. Constant and variable bit rate. Sampling rate from 8 kHz up to 48 kHz.	PIR sensor Passive infrared (PIR) motion sensor. Max range: 6 m (19.7 ft)	
System on chip (SoC)		Operating conditions -20 °C to 50 °C (4 °F to 122 °F) Humidity 10–85% RH (condensing)	
Model	i.MX 6ULL	Storage conditions -40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)	
Memory	256 MB RAM, 512 MB Flash	Approvals EMC EN 55032 Class B, EN 55035, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, ICES-3(B)/NMB-3(B), RCM AS/NZS CISPR 32 Class B, VCCI Class B Safety IEC/EN/UL 62368-1	
Network		Dimensions Ø182 X 52 mm (7.2 x 2.1 in)	
Network protocols	IPv4/v6 ^a , HTTP, HTTPS, SSL/TLS, QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, NTCIP, SIP (Cisco, Avaya, Asterisk)	Weight 600 g (1.3 lb)	
System integration		Included accessories Installation Guide, AVHS authentication key	
Application Programming Interface	Open API for software integration, including VAPIX®, One-click cloud connection, AXIS Camera Application Platform (ACAP).	Optional accessories AXIS T91A33 Lighting Track Mount, AXIS T91A23 Tile Grid Ceiling Mount, AXIS TC1601 Universal Mount For more accessories, see axis.com	
Video management systems	Compatible with AXIS Camera Station Edge, AXIS Camera Station Pro, AXIS Camera Station 5, and video management software from Axis' partners available at axis.com/vms .	Mounting option When you mount the device on a soft tile ceiling, use a plate behind the tile for reinforcement.	
VoIP	Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems. Peer to peer or integrated with SIP/PBX. Tested with: SIP client such as Cisco, Bria and Grandstream and PBX suppliers such as Cisco and Asterisk. Supported SIP features: secondary SIP server, IPv6, SRTP, SIPS, SIP TLS, DTMF (RFC2976 and RFC2833), NAT (ICE, STUN, TURN)	Languages English, German, French, Spanish, Italian	
		Warranty 5-year warranty, see axis.com/warranty	

a. Audio synchronization with IPv4 only.