

# AXIS W100 Body Worn Camera

Body worn camera from Axis

AXIS W100 Body Worn Camera is an easy-to-use, lightweight and robust body worn camera with an operating time of up to 17 hours. It delivers sharp images even in challenging conditions and has dual microphones for excellent audio and noise suppression. AXIS W100 features the Klick Fast System, making it compatible with most available mounting options. In addition, Axis Zipstream technology allows users to store as much footage as they require without compromising image quality. The camera also features a GPS/GNSS receiver for location data, Bluetooth<sup>®</sup> Low Energy 4.1, IEEE 802.11b/g/n, and a 6-axis gyro and accelerometer.

- > [Operating time of up to 17 hours](#)
- > [Klick Fast System](#)
- > [WDR](#)
- > [Dual microphones for noise suppression](#)
- > [3-year warranty](#)



# AXIS W100 Body Worn Camera

<b>Camera</b>		<b>Recording</b>	Configurable audio and video prebuffer 0, 15, 30, 60, 90, and 120 seconds <sup>c</sup> Configurable audio and video postbuffer 0, 10, 30, and 60 seconds
<b>Image sensor</b>	1/2.9" progressive scan RGB CMOS Sensitivity: 0.1 lux	<b>Positioning system</b>	GPS
<b>Lens</b>	Focal length, 2.1 mm Horizontal field of view: 141° Vertical field of view: 82° Fixed iris, F2.1	<b>Sensor</b>	6-axis gyroscope, accelerometer
<b>Shutter speed</b>	1/32000 s to 1/25 s with 50 Hz 1/32000 s to 1/30 s with 60 Hz	<b>User interface</b>	Status indicators Audio and vibration feedback
<b>Video</b>		<b>Wireless interface</b>	Bluetooth® Low Energy 4.1 IEEE 802.11b/g/n @ 2.4 GHz channels 1–11
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC) High Profile	<b>Cybersecurity</b>	Signed firmware CJIS compliant encrypted internal storage (AES256)
<b>Resolution</b>	1920x1080, 1280x720	<b>Casing</b>	IP67-rated Plastic casing Drop tested up to 2 m
<b>Frame rate</b>	25 fps at 50 Hz 30 fps at 60 Hz	<b>Color</b>	Black NCS S 9000-N
<b>WDR</b>	WDR	<b>Mounting</b>	Klick Fast™ System
<b>Video streaming</b>	Axis Zipstream for body worn	<b>Sustainability</b>	PVC free
<b>Audio</b>		<b>Connectors</b>	Pogo pin pads USB (for Axis accessories and charging using a cable with a USB Type-C® connector)
<b>Audio encoding</b>	AAC-LC Mono: 48 kHz, 64 kbps Stereo: 48 kHz, 128 kbps	<b>Operating conditions</b>	Temperature: -20 °C to 55 °C (-4 °F to 131 °F) Humidity: 10–100% RH (condensing)
<b>Audio input/output</b>	Built-in dual microphones	<b>Charging conditions</b>	Temperature: 0 °C to 35 °C (32 °F to 95 °F) Humidity: 5–95% RH (non-condensing)
<b>Approvals</b>		<b>Storage conditions</b>	Temperature (< 3 months): -20 °C to 45 °C (-4 °F to 113 °F) Temperature (> 3 months): 23 °C to 27 °C (73 °F to 81 °F) Optimal temperature: 25 °C (77 °F) Humidity: 5–95% RH (non-condensing)
<b>Supply chain</b>	TAA compliant	<b>Dimensions</b>	Height: 94 mm (3.7 in) Width: 68 mm (2.7 in) Depth: 27 mm (1.1 in)
<b>EMC</b>	EN 55032 Class B, EN 55035, EN 61000-6-1, EN 61000-6-2 Australia/New Zealand: RCM AS/NZS CISPR 32 Class B Canada: ICES-3(B)/NMB-3(B) USA: FCC Part 15 Subpart B Class B	<b>Weight</b>	174 g (0.38 lb)
<b>Safety</b>	IEC/EN/UL 62368-1, EN 50360	<b>Included accessories</b>	AXIS TW1100 Clip Mount AXIS TW1106 Magnet Mount
<b>Environment</b>	IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-78, IEC/EN 60529 IP67 MIL-STD-810H (Method 501.7, 503.7, 505.7, 509.7, 512.6, 516.8)	<b>Optional accessories</b>	Klick Fast™ System for Body worn camera mounts, AXIS TW1200 Body Worn Mini Bullet Sensor, AXIS TW1201 Body Worn Mini Cube Sensor AXIS Body Worn Assistant app for Android, iOS For more accessories, see <a href="http://axis.com/bodyworn">axis.com/bodyworn</a>
<b>Wireless</b>	EN 300328, EN 301489-1, EN 301489-17, EN 303413, FCC Part 15 Subpart C, RSS-247	<b>Warranty</b>	3-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a> . The 3-year warranty covers manufacturing defects in the product, including the battery. Do not replace the 3.7 V ID1058 battery during the period under which the Axis Hardware Product is covered by the Axis 3-year Limited Hardware Warranty. Replacement of the battery carried out by any other party than Axis during the warranty period voids the main item's warranty. Contact Axis Support or your reseller for matters regarding the battery or other service-related matters.
<b>Cybersecurity</b>	ETSI EN 303 645, BSI IT Security Label		
<b>Cybersecurity</b>			
<b>Edge security</b>	Software: Signed OS, AES-XTS-Plain64 256bit encryption		
<b>Network security</b>	IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2), HTTPS/HSTS <sup>a</sup> , TLS v1.2/v1.3 <sup>b</sup>		
<b>Documentation</b>	Axis body worn cameras – system security white paper, available at <a href="http://axis.com/learning/white-papers">axis.com/learning/white-papers</a> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> AXIS OS Software Bill of Material (SBOM) To download documents, go to <a href="http://axis.com/support/cybersecurity/resources">axis.com/support/cybersecurity/resources</a> To read more about Axis cybersecurity support, go to <a href="http://axis.com/cybersecurity">axis.com/cybersecurity</a>		
<b>General</b>			
<b>Battery</b>	Li-ion, 3600 mAh Up to 17 hours operating time in 720p Up to 15 hours operating time in 1080p		
<b>Storage</b>	64 GB non-volatile memory, up to 30 hours of recorded video AES256 encryption standard		
<b>Throughput</b>	Camera to system controller: 100 Mbit/s		

- This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. ([openssl.org](http://openssl.org)), and cryptographic software written by Eric Young ([ey@cryptsoft.com](mailto:ey@cryptsoft.com)).
- This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. ([openssl.org](http://openssl.org)), and cryptographic software written by Eric Young ([ey@cryptsoft.com](mailto:ey@cryptsoft.com)).
- In complex scenes, when using maximum resolution and 90 seconds pre-buffer, the actual pre-buffer time might be slightly shorter than configured.