

Optional M12-mount lenses

Greater flexibility for specific surveillance needs

Axis network cameras are equipped with carefully selected lenses to provide the best possible performance and durability. M12 lens option offers great flexibility for specific surveillance needs. The different properties enable a variety of areas of use, from wide area coverage to in-detail focus closeups – all with maintained image quality. The match between a lens, the image sensor is crucial to ensure the optimal camera performance. Therefore choosing the best lens option is of great importance for the quality of the surveillance. These M12 lenses are specifically adapted for onboard placed cameras.

- > Tested and approved for Axis cameras with M12-mount
- > Great image quality maintained



WWW.CXIS.COM T10213438/EN/M1.4/2408

Lens M12 2.1 mm				
Part number Properties	5901-371 Fixed iris 2.1 mm, F2.2 M12-mount		Dimensions	IR coating For compatible products, go to www.axis.com L x Ø: 19 x 16 mm (0.7 x 0.6 in)
		AXIS Lens M12 M	egapixe	l 2.8 mm
Part number Properties	03074-001 Fixed iris 2.8 mm, F1.2 M12-mount		Dimensions	IR coating For compatible products, go to www.axis.com L x Ø: 12.5 x 15 mm (0.5 x 0.6 in)
Lens M12 3.6 mm				
Part number Properties	5506-011 Fixed iris 3.6 mm, F2.0 M12-mount		Dimensions	IR coating For compatible products, go to www.axis.com L x Ø: 12 x 15 mm (0.5 x 0.6 in)
Lens M12 Megapixel 6 mm				
Part number Properties	5504-961 Fixed iris 6 mm, F1.6 M12-mount		Dimensions	IR coating For compatible products, go to www.axis.com L x Ø: 19 x 14 mm (0.7 x 0.5 in)
Lens M12 Megapixel 8 mm				
Part number Properties	5504-971 Fixed iris 8 mm, F1.6 M12-mount		Dimensions	IR coating For compatible products, go to www.axis.com L x Ø: 17 x 14 mm (0.7 x 0.5 in)

