

# AXIS M4215-LV Dome Camera

## Varifocal 2 MP dome with IR and deep learning

Featuring Lightfinder, WDR, and OptimizedIR, this compact and discreet dome delivers great image quality—day and night, even in low light. A deep learning processing unit (DLPU) lets you take advantage of intelligent analytics based on deep learning on the edge. Designed to blend into any environment, it can be repainted and offers a range of accessories for discreet monitoring. Plus, it features an HDMI port and the flexibility to add audio and I/O connectivity using AXIS T61 Series. Furthermore, Axis Edge Vault provides a hardware-based cybersecurity platform that safeguards the device.

- > **Great image quality in 2 MP**
- > **Varifocal lens with remote zoom and focus**
- > **Lightfinder, WDR and OptimizedIR**
- > **Analytics with deep learning**
- > **HDMI output for public viewing monitors**




# AXIS M4215-LV Dome Camera

<b>Camera</b>	
Image sensor	1/2.8" progressive scan RGB CMOS
Lens	Varifocal, 3.5–6.6 mm, F1.7 – 2.6 Horizontal field of view: 93°–47° Vertical field of view: 50°–26° Minimum focus distance: 1.5 m (59 in)
Day and night	Automatic IR-cut filter
Minimum illumination	With Lightfinder: Color: 0.14 lux at 50 IRE F1.7 B/W: 0.03 lux at 50 IRE F1.7, 0 lux when IR illumination is on
Shutter speed	1/25000 s to 1/5 s
Camera adjustment	Pan ±180°, tilt –40 to +65°, rotation ±105° Can be directed in any direction and see the wall/ceiling
<b>System on chip (SoC)</b>	
Model	CV25
Memory	1024 MB RAM, 512 MB Flash
Compute capabilities	Deep learning processing unit (DLPU)
<b>Video</b>	
Video compression	H.264 (MPEG-4 Part 10/AVC) Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG
Resolution	1920x1080 to 320x240
Frame rate	Up to 25/30 fps with power line frequency 50/60 Hz in H.264 and H.265 <sup>a</sup>
Video streaming	Multiple, individually configurable streams <sup>b</sup> Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265
Multi-view streaming	2 individually cropped out view areas
HDMI output	HDMI 1080p (16:9) @25/30 Hz refresh rate HDMI 720p (16:9) @50/60 Hz refresh rate
Noise reduction	Spatial filter (2D noise reduction) Temporal filter (3D noise reduction)
Image settings	Compression, color, brightness, sharpness, contrast, white balance, exposure control, motion-adaptive exposure, WDR: up to 110 dB depending on scene, text and image overlay, mirroring of images, privacy mask Rotation: 0°, 90°, 180°, 270°, including Corridor Format
Pan/Tilt/Zoom	Digital PTZ
<b>Audio</b>	
Audio input/output	Audio features through portcast technology: two-way audio connectivity, voice enhancer
<b>Network</b>	
Network protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS <sup>c</sup> , TLS <sup>d</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP <sup>e</sup> , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SRTP/RTSPS, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCP, ARP, SSH, LLDP, CDP, MQTT v3.1.1, Link-Local address (ZeroConf)
<b>System integration</b>	
Application Programming Interface	Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="http://axis.com">axis.com</a> One-click cloud connection ONVIF <sup>®</sup> Profile G, M, S and T, specification at <a href="http://onvif.org">onvif.org</a> Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX.
Video management systems	Compatible with AXIS Camera Station Edge, AXIS Camera Station Pro, AXIS Camera Station 5, and video management software from Axis' partners available at <a href="http://axis.com/vms">axis.com/vms</a> .
Onscreen controls	Privacy masks Media clip IR illumination
Event conditions	Application

Device status:	above operating temperature, above or below operating temperature, below operating temperature, within operating temperature, IP address removed, new IP address, network lost, system ready, live stream active
Edge storage:	recording ongoing, storage disruption, storage health issues detected
I/O:	manual trigger, virtual input
MQTT:	subscribe
Scheduled and recurring:	schedule
Video:	average bitrate degradation, day-night mode, tampering
<b>Event actions</b>	
Day-night mode	
MQTT:	publish
Notification:	HTTP, HTTPS, TCP and email
Overlay text	
Pre- and post-alarm video or image buffering for recording or upload	
Recordings:	SD card and network share
SNMP traps:	send, send while the rule is active
Upload of images or video clips:	FTP, SFTP, HTTP, HTTPS, network share and email
WDR mode	
<b>Built-in installation aids</b>	
Pixel counter, remote zoom and focus, level grid	
<b>Analytics</b>	
<b>Applications</b>	
Included	AXIS Object Analytics, AXIS Scene Metadata, AXIS Face Detector, AXIS Video Motion Detection, AXIS Live Privacy Shield
Supported	AXIS People Counter AXIS Queue Monitor AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://axis.com/acap">axis.com/acap</a>
<b>AXIS Object Analytics</b>	
Object classes:	humans, vehicles (types: cars, buses, trucks, bikes)
Scenarios:	line crossing, object in area, occupancy in area, time in area
Up to 10 scenarios	
Other features:	triggered objects visualized with color-coded bounding boxes Polygon include/exclude areas Perspective configuration ONVIF Motion Alarm event
<b>AXIS Scene Metadata</b>	
Object classes:	humans, faces, vehicles (types: cars, buses, trucks, bikes), license plates
Object attributes:	vehicle color, upper/lower clothing color, confidence, position
<b>Approvals</b>	
<b>Product markings</b> CSA, UL/cUL, BIS, UKCA, CE, KC, EAC, VCCI, RCM	
<b>EMC</b>	
CISPR 35, CISPR 32 Class A, EN 55035, EN 55032 Class A, EN 61000-6-1, EN 61000-6-2	
USA:	FCC Part 15 Subpart B Class A
Canada:	ICES-3(A)/NMB-3(A)
Korea:	KS C 9835, KS C 9832 Class A
Australia/New Zealand:	RCM AS/NZS CISPR 32 Class A
Japan:	VCCI Class A
<b>Safety</b>	
IEC/EN/UL 62368-1, CAN/CSA C22.2 No. 62368-1, IS 13252 IEC/EN 62471	
<b>Environment</b>	
IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC/EN 60529 IP42, IEC/EN 62262 IK08	
<b>Network</b>	
NIST SP500-267	
<b>Cybersecurity</b>	
ETSI EN 303 645, BSI IT Security Label	
<b>Cybersecurity</b>	
<b>Edge security</b>	
Software:	Signed OS, brute force delay protection, digest authentication and OAuth 2.0 RFC6749 OpenID Authorization Code Flow for centralized ADFS account management, password protection, AES-XTS-Plain64 256bit SD card encryption
Hardware:	Axis Edge Vault cybersecurity platform Secure element (CC EAL 6+), system-on-chip security (TEE), Axis device ID, secure keystore, signed video, secure boot, encrypted filesystem (AES-XTS-Plain64 256bit)

<b>Network security</b>	IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2) <sup>6</sup> , IEEE 802.1AE (MACsec PSK/EAP-TLS), IEEE 802.1AR, HTTPS/HSTS <sup>7</sup> , TLS v1.2/v1.3 <sup>9</sup> , Network Time Security (NTS), X.509 Certificate PKI, host-based firewall	AXIS T91A23 Tile Grid Ceiling Mount AXIS TM4101 Pendant Kit AXIS TM3101 Pendant Wall Mount AXIS Surveillance Cards For more accessories, go to <a href="https://axis.com/products/axis-m4215-lv#accessories">axis.com/products/axis-m4215-lv#accessories</a>
<b>Documentation</b>	<i>AXIS OS Hardening Guide</i> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> AXIS OS Software Bill of Material (SBOM) To download documents, go to <a href="https://axis.com/support/cybersecurity/resources">axis.com/support/cybersecurity/resources</a> To read more about Axis cybersecurity support, go to <a href="https://axis.com/cybersecurity">axis.com/cybersecurity</a>	
<b>General</b>		
<b>Casing</b>	IP42 ingress protection, IK08 impact-resistant, polycarbonate and aluminum casing with hard-coated dome Encapsulated electronics Color: white NCS S 1002-B For repainting instructions of casing and impact on warranty, contact your Axis partner.	
<b>Power</b>	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Typical 4.8 W, max 9.5 W	
<b>Connectors</b>	RJ45 10BASE-T/100BASE-TX PoE HDMI type D Audio: Audio and I/O connectivity via portcast technology	
<b>IR illumination</b>	OptimizedIR with power-efficient, long-life 850 nm IR LEDs Range of reach 20 m (65 ft) or more depending on the scene	
<b>Storage</b>	Support for microSD/microSDHC/microSDXC card Recording to network-attached storage (NAS) For SD card and recorder recommendations, see <a href="https://axis.com">axis.com</a>	
<b>Operating conditions</b>	0 °C to 45 °C (32 °F to 113 °F) Humidity 10–85% RH (non-condensing)	
<b>Storage conditions</b>	–30 °C to 65 °C (–22 °F to 149 °F) Humidity 5–95% RH (non-condensing)	
<b>Dimensions</b>	Height: 71 mm (2.8 in) ø 120 mm (4.72 in)	
<b>Weight</b>	366 g (0.81 lb)	
<b>Box content</b>	Camera, installation guide, owner authentication key, virtual client license for H.264/H.265	
<b>Optional accessories</b>	AXIS T8415 Wireless Installation Tool AXIS TM4201 Recessed Mount AXIS TM3207 Recessed Mount AXIS T94C01L Recessed Mount AXIS T94C01U Universal Mount AXIS T94C01M J-Box/Gang Box Plate AXIS M42 Casing A Black 4P AXIS M42 Smoked Dome A 4P AXIS T91A33 Lighting Track Mount	
<b>System tools</b>	AXIS Site Designer, AXIS Device Manager, product selector, accessory selector, lens calculator Available at <a href="https://axis.com">axis.com</a>	
<b>Languages</b>	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese, Dutch, Czech, Swedish, Finnish, Turkish, Thai, Vietnamese	
<b>Warranty</b>	5-year warranty, see <a href="https://axis.com/warranty">axis.com/warranty</a>	
<b>Part numbers</b>	Available at <a href="https://axis.com/products/axis-m4215-lv#part-numbers">axis.com/products/axis-m4215-lv#part-numbers</a>	
<b>Sustainability</b>		
<b>Substance control</b>	PVC free, BFR/CFR free in accordance with JEDEC/ECA Standard J5709 RoHS in accordance with EU RoHS Directive 2011/65/EU/ and EN 63000:2018 REACH in accordance with (EC) No 1907/2006. For SCIP UUID, see <a href="https://echa.europa.eu">echa.europa.eu</a>	
<b>Materials</b>	Renewable carbon-based plastic content: 40.3% (recycled) Screened for conflict minerals in accordance with OECD guidelines To read more about sustainability at Axis, go to <a href="https://axis.com/about-axis/sustainability">axis.com/about-axis/sustainability</a>	
<b>Environmental responsibility</b>	<a href="https://axis.com/environmental-responsibility">axis.com/environmental-responsibility</a> Axis Communications is a signatory of the UN Global Compact, read more at <a href="https://unglobalcompact.org">unglobalcompact.org</a>	
		<p>a. <i>Reduced frame rate in Motion JPEG</i></p> <p>b. <i>We recommend a maximum of 3 unique video streams per camera or channel, for optimized user experience, network bandwidth, and storage utilization. A unique video stream can be served to many video clients in the network using multicast or unicast transport method via built-in stream reuse functionality.</i></p> <p>c. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).</i></p> <p>d. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).</i></p> <p>e. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).</i></p> <p>f. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).</i></p> <p>g. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).</i></p>

# Dimension drawing



## Detect, Observe, Recognize, Identify (DORI)

	DORI definition	Distance (wide)	Distance (tele)
Detect	25 px/m (8 px/ft)	48.78 m (160.0 ft)	92.23 m (302.5 ft)
Observe	63 px/m (19 px/ft)	19.34 m (63.44 ft)	36.59 m (120.0 ft)
Recognize	125 px/m (38 px/ft)	9.72 m (31.9 ft)	18.43 m (60.45 ft)
Identify	250 px/m (76 px/ft)	4.81 m (15.8 ft)	9.19 m (30.1 ft)

The DORI values are calculated using pixel densities for different use cases as recommended by the EN-62676-4 standard. The calculations use the center of the image as the reference point and consider lens distortion. The possibility to recognize or identify a person or object depends on factors such as object motion, video compression, lighting conditions, and camera focus. Use margins when planning. The pixel density varies across the image, and the calculated values can differ from the distances in the real world.

## Highlighted capabilities

### AXIS Object Analytics

AXIS Object Analytics is a preinstalled, multifeatured video analytics that detects and classifies humans, vehicles, and types of vehicles. Thanks to AI-based algorithms and behavioral conditions, it analyzes the scene and their spatial behavior within – all tailored to your specific needs. Scalable and edge-based, it requires minimum effort to set up and supports various scenarios running simultaneously.

### Axis Edge Vault

Axis Edge Vault is the hardware-based cybersecurity platform that safeguards the Axis device. It forms the foundation that all secure operations depend on and offer features to protect the device's identity, safeguard its integrity and protect sensitive information from unauthorized access. For instance, **secure boot** ensures that a device can boot only with **signed OS**, which prevents physical supply chain tampering. With signed OS, the device is also able to validate new device software before accepting to install it. And the **secure keystore** is the critical building-block for protecting cryptographic information used for secure communication (IEEE 802.1X, HTTPS, Axis device ID, access control keys etc.) against malicious extraction in the event of a security breach. The secure keystore and secure connections are provided through a Common Criteria or FIPS 140 certified hardware-based cryptographic computing module.

Furthermore, signed video ensures that video evidence can be verified as untampered. Each camera uses its unique video signing key, which is securely stored in the secure keystore, to add a signature into the video stream allowing video to be traced back to the Axis camera from where it originated.

To read more about Axis Edge Vault, go to [axis.com/solutions/edge-vault](https://axis.com/solutions/edge-vault).

### Lightfinder

The Axis Lightfinder technology delivers high-resolution, full-color video with a minimum of motion blur even in near darkness. Because it strips away noise, Lightfinder makes dark areas in a scene visible and captures details in very low light. Cameras with Lightfinder discern color in low light better than the human eye. In surveillance, color may be the critical factor to identify a person, an object, or a vehicle.

### OptimizedIR

Axis OptimizedIR provides a unique and powerful combination of camera intelligence and sophisticated LED technology, resulting in our most advanced camera-integrated IR solutions for complete darkness. In our pan-tilt-zoom (PTZ) cameras with OptimizedIR, the IR beam automatically adapts and becomes wider or narrower as the camera zooms in and out to make sure that the entire field of view is always evenly illuminated.

### Zipstream

The Axis Zipstream technology preserves all the important forensic in the video stream while lowering bandwidth and storage requirements by an average of 50%. Zipstream also includes three intelligent algorithms, which ensure that relevant forensic information is identified, recorded, and sent in full resolution and frame rate.

For more information, see [axis.com/glossary](https://axis.com/glossary)