

AXIS P1377-LE Network Camera

Fully-equipped 5 MP surveillance for the great outdoors

With a robust design, AXIS P1377-LE offers excellent 5 MP video and can withstand extreme temperatures ranging from -40 °C to 60 °C (-40 °F to 140 °F). For extra protection an optional weathershield is available. It delivers great details in challenging or low light and includes Axis OptimizedIR for surveillance in pitch darkness. Designed as a deterrent, it includes electronic image stabilization, shock detection, tampering alarm and video streaming indicator. Axis Zipstream supporting H.264/H.265 provides exceptional savings on bandwidth and storage. Plus, with CS mount and support for motorized i-CS, you can easily change lens to meet your requirements.

- > 30 fps in 5 MP or up to 180 fps in HDTV 720p
- > OptimizedIR and Forensic WDR
- > Signed firmware and secure boot
- > Electronic image stabilization
- > Zipstream supporting H.264 and H.265



AXIS P1377-LE Network Camera

Camera		ONVIF® Profile G, ONVIF® Profile M, ONVIF® Profile S and ONVIF® Profile T, specification at onvif.org
Image sensor	1/2.7" progressive scan RGB CMOS	
Lens	IR corrected, CS-mount lens, P-Iris Varifocal 2.8–8 mm, F1.2 Horizontal field of view: 90°–38° Vertical field of view: 67°–28°	Onscreen controls Electronic image stabilization Day/night shift Defogging Wide dynamic range
Day and night	Automatically removable infrared-cut filter	Event triggers Analytics, shock detection, open casing, edge storage events, supervised external input, audio level, time scheduled MQTT subscribe
Minimum illumination	5 MP 25/30 fps with Forensic WDR and Lightfinder: Color: 0.13 lux, at 50 IRE F1.2 B/W: 0.03 lux, at 50 IRE F1.2 0 lux with IR illumination on	Event actions File upload: FTP, SFTP, HTTP, HTTPS, network share and email Notification: email, HTTP, HTTPS and TCP External output activation Video recording to edge storage, Play audio clip Pre- and post-alarm video buffering PTZ preset, Guard tour, Overlay text Day/Night switching, Status LED activation MQTT publish Send SNMP trap
Shutter speed	WDR: 1/33500 s to 1/5 s No WDR: 1/50000 s to 1/5 s	Built-in installation aids Focus assistant, pixel counter, remote back focus, autorotation, remote focus and zoom and with optional i-CS lens.
System on chip (SoC)		Analytics
Model	ARTPEC-7	Applications Included AXIS Object Analytics, AXIS Scene Metadata, AXIS Live Privacy Shield ^a , AXIS Video Motion Detection Supported AXIS Perimeter Defender, AXIS License Plate Verifier Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap
Memory	1 GB RAM, 512 MB Flash	AXIS Object Analytics Object classes: humans, vehicles Scenarios: line crossing, object in area, crossline counting, time in area Up to 10 scenarios Other features: triggered objects visualized with trajectories, color-coded bounding boxes and tables Polygon include/exclude areas Perspective configuration ONVIF Motion Alarm event
Compute capabilities	Machine learning processing unit (MLPU)	AXIS Scene Metadata Object classes: humans, faces, vehicles (types: cars, buses, trucks, bikes), license plates Confidence, position
Video		Cybersecurity
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Motion JPEG Controllable frame rate and bandwidth	Edge security Software: Signed OS, brute force delay protection, digest authentication and OAuth 2.0 RFC6749 OpenID Authorization Code Flow for centralized ADFS account management, password protection, AES-XTS-Plain64 256bit SD card encryption Hardware: Secure boot
Resolution	2592x1944 (5 MP) to 160x90 2688x1512 (4 MP) to 160x90 1920x1080 (HDTV 1080p) to 160x90 1280x720 (HDTV 720p) to 160x90	Network security IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2), IEEE 802.1AE (MACsec PSK/EAP-TLS), HTTPS/HSTS, TLS v1.2/v1.3, Network Time Security (NTS), X.509 Certificate PKI, host-based firewall
Frame rate	Capture mode 5 MP: 25/30 fps (50/60 Hz) Capture mode 4 MP: 25/30 fps (50/60 Hz) Capture mode HDTV 720p: 180 fps	Documentation <i>AXIS OS Hardening Guide</i> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> AXIS OS Software Bill of Material (SBOM) To download documents, go to axis.com/support/cybersecurity/resources To read more about Axis cybersecurity support, go to axis.com/cybersecurity
Video streaming	Multiple, individually configurable streams in H.264, H.265, and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 Low latency mode Video streaming indicator	General
Multi-view streaming	Up to 8 individually cropped out view areas	Casing IP66-, IP67- and NEMA 4X-rated, IK10 impact-resistant polymer enclosure with aluminium base and intrusion alarm switch Weathershield with black anti-glare coating Color: White NCS S 1002-B
Image settings	Saturation, contrast, brightness, sharpness, Forensic WDR: Up to 120 dB depending on scene, white balance, day/night threshold, exposure mode, exposure zones, local contrast, tone mapping, compression, orientation: auto, 0°, 90°, 180°, 270° including Corridor Format, mirroring of images, dynamic text and image overlay, privacy masks, defogging, electronic image stabilization, barrel distortion correction, scene profiles: forensic, vivid, traffic overview	Sustainability PVC free
Pan/Tilt/Zoom	Digital PTZ Uploadable PTZ driver (Pelco D pre-installed)	Power 12–28 V DC, max 25.5 W (incl. IR and front heater), typical 10.5 W Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 4, max 25.5 W (incl. IR and front heater), typical 11.1 W Power redundancy
Audio		Connectors RJ45 10BASE-T/100BASE-TX/1000BASE-T
Audio streaming	Two-way, full duplex	
Audio encoding	AAC LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz, LPCM 8/16/32/48 kHz Configurable bit rate	
Audio input/output	External microphone input, line input, digital input with ring power, line output, automatic gain control	
Network		
Network protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS, HTTP/2, TLS, QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SFTP, SRTP/RTSPS, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SSH, LLDP, CDP, MQTT v3.1.1, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf)	
System integration		
Application Programming Interface	Open API for software integration, including VAPIX® and AXIS Camera Application Platform, specifications at axis.com AXIS Video Hosting System (AVHS) with One-Click Connection One-click cloud connection	

	I/O: 6-pin 2.5 mm terminal block, for 2 supervised alarm inputs and 2 outputs RS485/RS422, 2 pcs, 2 pos, full duplex, terminal block DC input, terminal block 3.5 mm mic/line in, 3.5 mm line out i-CS connector (compatible with P-Iris and DC-iris)
IR illumination	OptimizedIR with power-efficient, long-life 850 nm IR LEDs Range 50 m (164 ft) or more, depending on the scene
Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Operating conditions	-40 °C to 60 °C (-40 °F to 140 °F) Maximum temperature according to NEMA TS 2 (2.2.7): 74 °C (165 °F) Humidity 10–100% RH (condensing) Wind load (sustained): 55 m/s (123 mph)
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
Approvals	EMC EN 55032 Class A, EN 50121-4, IEC 62236-4, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KCC KN32 Class A, KN35 Safety IEC/EN/UL 62368-1, CAN/CSA C22.2 No. 62368-1, IEC/EN/UL 60950-22, CAN/CSA-C22.2 No. 60950-22, IEC 62471, IS 13252 Environment IEC/EN 60529 IP66/IP67, NEMA 250 Type 4X, NEMA TS 2 (2.2.7-2.2.9), IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 62262 IK10

	Network NIST SP500-267
Dimensions	404 x 159 x 168 mm (15.9 x 6.3 x 6.6 in)
Weight	2.4 kg (5.3 lb)
Included accessories	Installation guide, Windows® decoder 1-user license, wall mount bracket, sunshield, connector kit IK10 tool Torx® T20 screw driver, Torx® T30 screw bit AXIS P13 Weathershield Kit A Pre-mounted AXIS Fixed Box IR Illuminator Kit A
Optional lenses	Lens Computar i-CS 2.8–8.5 mm Lens CS 4–10 mm F0.9 P-Iris Lens i-CS 9–50 mm F1.5 8 MP Tamron 5MP Lens P-Iris 8–50 mm F1.6 Theia Varifocal Ultra Wide Lens 1.8–3.0 mm
Optional accessories	Axis mounts, Axis lenses, Axis midspans, Axis microphones AXIS P13 Weathershield Extension A AXIS T8355 Digital Microphone AXIS T99A10 Positioning Unit 24 V AC/DC For more accessories, see axis.com
Video management software	AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available at axis.com/vms
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese, Dutch, Czech, Swedish, Finnish, Turkish, Thai, Vietnamese
Warranty	5-year warranty, see axis.com/warranty

a. Available for download