

# AXIS T8154 60 W SFP Midspan

For network or fiber installations

AXIS T8154 60 W SFP Midspan is a compact, plug-and-play media converter with PoE. With its integrated power supply, it minimizes the amount of cabling and facilitates installation. AXIS T8154 offers data input through SFP or RJ45, and delivers PoE up to 60 W. It works with all Axis network products supporting Power over Ethernet.

- > **SFP slot for fiber**
- > **Integrated midspan**
- > **PoE up to 60 W**
- > **Support for all Axis network products**



**Data**

A black horizontal line with solid black circles at both ends, representing a data connection.

**PoE**

A yellow horizontal line with solid yellow circles at both ends, representing a PoE connection.

## AXIS T8154 60 W SFP Midspan

Midspans		General	
<b>Function</b>	Data and power are fed to a network video product through an Ethernet cable Use together with a PoE splitter for a network video product without built-in PoE support	<b>Sustainability</b>	PVC free
<b>Data rate</b>	10/100/1000 Mbps	<b>Display and indicators</b>	LEDs are located on the front panel PoE LED Power LED
<b>Installation and management</b>	Automatically detects PoE and High PoE-enabled devices and supplies inline power Local LED management display	<b>Mounting</b>	Wall, shelf or DIN rail <sup>b</sup> Can be mounted inside AXIS Wall Mount or an equivalent product
Data & power		<b>Operating conditions</b>	Up to 30 W: -10 °C to 55 °C (14 °F to 131 °F) Up to 60 W: -10 °C to 45 °C (14 °F to 113 °F) When mounted inside AXIS T91G61 or similar and connected to an outdoor PTZ: -50 °C to 50 °C (-58 °F to 122 °F) Humidity max 90% RH (non-condensing)
<b>Power</b>	IEEE802.3bt Type 3 Class 6 compatible <sup>a</sup> , High Power over Ethernet, max 60 W	<b>Storage conditions</b>	-20 °C to 70 °C (-4 °F to 158 °F) Humidity max 95% RH (non-condensing)
<b>Input</b>	AC input voltage: 100 to 240 V AC AC frequency: 50–60 Hz	<b>Approvals</b>	<b>Safety</b> IEC/EN/UL 60950-1, EN 62368-1, KC, CCC, CB, S-Mark, GS Mark per EN 60950-1 <b>EMC</b> EN 55032 Class A, EN 61000 3-2, EN 61000 3-3, EN 55035, FCC Part 15 Subpart B Class A, VCCI Class A, RCM AS/NZS CISPR32 Class A, KCC KN32 Class A, KN35, EN 61000-6-1, EN 61000-6-2, EN 50121-4, IEC 62236-4
<b>Output</b>	55 V DC (max 60 W)	<b>Dimensions</b>	50 x 80 x 184 mm (2.0 x 3.1 x 7.2 in)
<b>Connectors</b>	Shielded RJ45, EIA 568A and 568B SFP slot Power connector C14	<b>Weight</b>	517 g (1.1 lb)
<b>Wiring</b>	Data provided over pairs 1/2 and 3/6 for 10/100 Ethernet, over all four pairs for Gigabit Ethernet Power over pairs 1/2 (-), 3/6 (+), 4/5 (+) and 7/8 (-)	<b>Included accessories</b>	Installation guide
		<b>Optional accessories</b>	AXIS T91A03 DIN Rail Clip Mains Cable Angle C13-Open 0.5 m AXIS T8611 SFP Module LC.LX AXIS T8612 SFP Module LC.SX AXIS T8613 SFP Module 1000BASE-T For more accessories, see <a href="http://axis.com">axis.com</a>
		<b>Warranty</b>	3-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>

a. Only applicable for 2675396

b. Sold as optional accessory