

AXIS D4100-E Network Strobe Siren

Deterrence, safety, operational efficiency

AXIS D4100-E is a fully networked strobe siren for numerous applications. Through VAPIX[®], MQTT or SIP, it connects to any Axis device, Axis VMS, or to third-party VMS to signal and alarm using strobe lighting and siren alarms. For instance, it's ideal for perimeter protection with AXIS Perimeter Defender, or for improved parking entrance management with a license plate recognition (LPR) camera. Including various sound clips and white/RGBA light patterns, it can be set up with profiles to trigger different responses. Powered with PoE, this robust, IP66-, NEMA-4X- and IK10-rated device comes with first-class quality, support, and a 5-year warranty.

- > [Light and sound in one IP-based device](#)
- > [Profiles with different priority levels](#)
- > [VAPIX, MQTT and SIP integration](#)
- > [IP66, IK10, NEMA-4X rated casing](#)
- > [5-year warranty](#)



AXIS D4100-E Network Strobe Siren

Light		Network security
Illumination LED	Red, blue, green, amber (RGBA) LEDs White LEDs, max 893 lm (PoE Class 4)/220 lm (PoE Class 3)	IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2) ^a , IEEE 802.1AR, HTTPS/HSTS ^a , TLS v1.2/v1.3 ^a , Network Time Security (NTS), X.509 Certificate PKI, host-based firewall
Siren		Documentation
Max sound pressure level	>110 dB, 1 m at 3.4 kHz	<i>AXIS OS Hardening Guide</i> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> AXIS OS Software Bill of Material (SBOM) To download documents, go to axis.com/support/cybersecurity/resources To read more about Axis cybersecurity support, go to axis.com/cybersecurity
Coverage pattern	150 degree coaxial at 2 kHz	
Network		General
Security	IP address filtering, HTTPS ^a encryption, IEEE 802.1x (EAP-TLS) ^a network access control, user access log, centralized certificate management, signed video, Axis Edge Vault, Axis device ID, secure keystore (CC EAL4 certified)	Casing
Network protocols	IPv4, IPv6, USGv6, ICMPv4/ICMPv6, HTTP, HTTPS ^a , HTTP/2, TLS ^a , SMTP, mDNS (Bonjour), UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, TCP, UDP, IGMPv1/v2/v3, RTP, DHCPv4/v6, SSH, SIP, LLDP, CDP, MQTT, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf)	IP66-, NEMA 4X- and IK10-rated Aluminum and plastic casing Color: white NCS S 1002-B
System integration		Mounting
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com One-click cloud connection Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX.	Mounting bracket with junction box holes (double-gang, single-gang, and 4" octagon) For wall and ceiling mount: ¼"-20 UNC tripod screw thread ½" conduit fitting with optional accessory
Event conditions	I/O: virtual input, manual trigger, digital input Light and siren: health check status Device status: operating temperature, system ready, network lost, new IP address, IP address removed MQTT: stateful, stateless Call: state change, state MQTT subscribe Scheduled and recurring: schedule	Sustainability
Event actions	SNMP trap message Light and siren: profiles, health check Status LED Notification: email, HTTP, HTTPS, TCP I/O: toggle MQTT Calls: SIP calls MQTT publish	PVC free
Data streaming	Event data	Memory
Approvals		256 MB RAM, 512 MB Flash
EMC	CISPR 32 Class A, EN 50121-4, EN 55032 Class A, EN 55035, EN 50130-4, EN 61000-6-1, EN 61000-6-2, IEC 62236-4 Australia/New Zealand: RCM AS/NZS CISPR 32 Class A Canada: ICES-3(A)/NMB-3(A) Japan: VCCI Class A Korea: KS C 9832 Class A, KS C 9835 USA: FCC Part 15 Subpart B Class A	Power
Safety	CAN/CSA-C22.2 No. 60950-22, CAN/CSA C22.2 No. 62368-1, IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, IEC 62471	Power over Ethernet (PoE) IEEE 802.3at Type 2 Class 4, max 25.5 W, typical 1.3 W Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 ^b , max 12.95 W, typical 1.3 W
Environment	IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP66, IEC/EN 62262 IK10, NEMA 250 Type 4X, MIL-STD-810H (Method 501.7, 502.7, 506.6, 507.6)	Connectors
Network	NIST SP500-267	Shielded RJ45 10BASE-T/100BASE-TX PoE I/O: 4-pin 2.5 mm terminal block (2 configurable inputs and outputs)
Cybersecurity	ETSI EN 303 645	Operating conditions
Cybersecurity		-40 °C to 60 °C (-40 °F to 140 °F) Start-up temperature: -40 °C (-40 °F) Humidity 10–100% RH (condensing)
Edge security	Software: Signed OS, brute force delay protection, digest authentication and OAuth 2.0 RFC6749 OpenID Authorization Code Flow for centralized ADFS account management, password protection, AES-XTS-Plain64 256bit SD card encryption Hardware: Axis Edge Vault cybersecurity platform Secure element (CC EAL 6+), Axis device ID, secure keystore, signed video, secure boot	Storage conditions
		-40 °C to 70 °C (-40 °F to 158 °F) Humidity 5–95% RH (non-condensing)
		Dimensions
		Height: 66 mm (2.6 in) ø 170 mm (6.7 in)
		Weight
		1000 g (2.2 lb)
		Included accessories
		Installation guide, Resistor [®] TR20 bit, terminal block connector, cable gaskets, connector guard
		Optional accessories
		D4100-E specific accessories TD4601 ACI Conduit Bracket, TD4801 Sunshield Other compatible accessories AXIS T8415 Wireless Installation Tool, T94K01D Pendant Kit, T94N01D Pendant Kit, T91B47 Pole Mount, T94R01B Corner Bracket, T91A64 Corner Bracket, T94V01C Dual Camera Mount, T91A33 Lighting Track Mount, T91A23 Tile Grid Ceiling Mount, T91A04 Camera Holder ¾" NPS, ACI Conduit Adapter 1/2"-3/4" NPS (together with TD4601 ACI Conduit Bracket), ACI Conduit Adapter 1/2" U-Shaped 20 mm (together with TD4601 ACI Conduit Bracket), AXIS Dome Intrusion Switch C For more accessories, see axis.com
		Video management systems
		Compatible with AXIS Camera Station Edge, AXIS Camera Station Pro, AXIS Camera Station 5, and video management software from Axis' partners available at axis.com/vms .
		Languages
		English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese, Dutch, Czech, Swedish, Finnish, Turkish, Thai, Vietnamese
		Warranty
		5-year warranty, see axis.com/warranty

- a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eyay@cryptsoft.com).
- b. With reduced light brightness