

AXIS Camera Station S2216 Appliance

All-in-one recorder with PoE switch for UHD surveillance

AXIS Camera Station S2216 Appliance is an all-in-one recording solution with integrated, manageable PoE switch designed to deliver reliable high-definition surveillance with up to 4K resolution. For quick and easy installation, AXIS S2216 is preconfigured and preloaded with AXIS Camera Station video management software, and includes licenses for 16 channels plus all necessary system software. AXIS Camera Station offers an intuitive user interface that allows users to take full advantage of Axis wide range of video surveillance cameras and other IP products. With the operating system stored on a solid-state drive (SSD) and 5-year warranty, AXIS S2216 provides a reliable surveillance solution.

- > [All-in-one solution with integrated PoE switch](#)
- > [High-definition surveillance with up to 4K resolution](#)
- > [AXIS Camera Station licenses included](#)
- > [Full compatibility with Axis products](#)



AXIS Camera Station S2216 Appliance

Licenses	16 AXIS Camera Station core licenses included and tied to the hardware. Can be upgraded with additional licenses (sold separately).	Supports the same split scenarios as live view Supports only one monitor Playback at high speeds can affect video performance.
System scalability	Qualified for up to 16 video channels and 32 doors	Recording Qualified for recording up to 16 video channels with a total recording rate up to 256 Mbit per second
Hardware		General
Processor	Intel® Core™ i5	Operating system Microsoft® Windows® 10 IoT Enterprise Operating system recovery: yes Operating system drive: 120 GB SSD
Memory	8 GB	Security Security support for encrypted operating system drive and recording drive FIPS 140-2 level 2 certified Trusted Platform Module (TPM 2.0)
Storage	Surveillance Class HDD Total HDD slot: 4 Free HDD slot: 2 Out-of-the-box storage: 8 TB (2x4 TB)	Operating conditions 0 °C to 40 °C (32 °F to 104 °F) Humidity: 10–90% RH (non-condensing)
RAID	Factory RAID level: Not configured RAID levels: 0, 1, 10	Storage conditions -40 °C to 65 °C (-40 °F to 149 °F)
Switch	16 ports integrated, 260 W total power budget Power over Ethernet (PoE) IEEE 802.3at Class 4	Approvals EMC CNS 13438, EAC, EN 55024, EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A
Graphics card	Intel® HD Graphics	Safety IEC/EN 60950-1, IEC/EN 62368-1, KC-Mark, UL 62368-1, IS 13252
Power	Max 520 W, 260 W PoE dedicated 100 – 240 V AC, 6.5–2.5 A, 50/60 Hz	Dimensions 476 x 440 x 45 mm (18.7 x 17.3 x 1.8 in), 1U chassis
Connectors	Front side: 1x USB 3.0 1x Audio line in 1x Audio line out Rear side Switch: 16x PoE ports 10/100 Mbps 1x SFP 10/100/1000 Mbps 1x RJ45 10/100/1000 Mbps Rear side Server: 1x RJ45 10/100/1000 Mbps 2x USB 2.0 1 Displayport™ 1 HDMI port	Weight 11 kg (24.3 lb)
Video		Included accessories Rack rails, power cord
Video streaming	Live view: 1 x 4K stream full screen 4 split x 1080p Up to 16 cameras split view Supports two monitors, maximum one 4K monitor recommended Playback:	Optional accessories Surveillance Hard Drive 4 TB available from Axis Axis desktop terminals Axis Ethernet surge protector For more accessories, see axis.com
		Warranty Recorder and hard drive: 5-year warranty, see axis.com/warranty
		Export control This product is subject to export control regulations, and you should always comply with all applicable national and international export or re-export control regulations.

AXIS Camera Station

This product does not support the free text search functionality due to limited RAM.
For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on axis.com