

AXIS M4216-LV Dome Camera

Varifocal 4 MP dome with IR and deep learning

Featuring Lightfinder, WDR, and OptimizedIR, this compact and discreet dome delivers great image quality—day and night, even in low light. A deep learning processing unit (DLPU) lets you take advantage of intelligent analytics based on deep learning on the edge. Designed to blend into any environment, it can be repainted and offers a range of accessories for discreet monitoring. Plus, it features an HDMI port and the flexibility to add audio and I/O connectivity using AXIS T61 Series. Furthermore, Axis Edge Vault protects your Axis device ID and simplifies authorization of Axis devices on your network.

- > **Great image quality in 4 MP**
- > **Varifocal lens with remote zoom and focus**
- > **Lightfinder, WDR, and OptimizedIR**
- > **Analytics with deep learning**
- > **HDMI output for public viewing monitors**



AXIS M4216-LV Dome Camera

| | | |
|-----------------------------------|--|---|
| Camera | | |
| Image sensor | 1/2.7" progressive scan RGB CMOS | |
| Lens | Varifocal, 3–6 mm, F1.9 – 2.7 Horizontal field of view: 100°–45° Vertical field of view: 72°–34° Remote focus and zoom, fixed iris | removed, network lost, new IP address, system ready, within operating temperature Edge storage: recording ongoing, storage disruption I/O: manual trigger, virtual input, digital input via AXIS T61 Audio and I/O Interfaces with portcast technology MQTT subscribe Scheduled and recurring: scheduled event Video: live stream open |
| Day and night | Automatic IR-cut filter | |
| Minimum illumination | With Lightfinder: Color: 0.18 lux at 50 IRE F2.0 B/W: 0.03 lux at 50 IRE F2.0, 0 lux when IR illumination is on | |
| Shutter speed | 1/37500 s to 1/5 s | |
| Camera adjustment | Pan ±180°, tilt –40 to +65°, rotation ±105° Can be directed in any direction and see the wall/ceiling | |
| System on chip (SoC) | | |
| Model | CV25 | |
| Memory | 1024 MB RAM, 512 MB Flash | |
| Compute capabilities | Deep learning processing unit (DLPU) | |
| Video | | |
| Video compression | H.264 (MPEG-4 Part 10/AVC) Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main and High Profiles Motion JPEG | |
| Resolution | 2304x1728 to 320x240 | |
| Frame rate | Up to 25/30 fps with power line frequency 50/60 Hz in H.264 and H.265 ^a | |
| Video streaming | Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/MBR H.264/H.265 Low latency mode HDMI | |
| Multi-view streaming | Up to 2 individually cropped out view areas in full frame rate | |
| HDMI output | HDMI 1080p (16:9) @25/30 Hz refresh rate HDMI 720p (16:9) @50/60 Hz refresh rate | |
| Image settings | Compression, color, brightness, sharpness, contrast, white balance, exposure control, motion-adaptive exposure, WDR: up to 110 dB depending on scene, text and image overlay, mirroring of images, privacy mask Rotation: 0°, 90°, 180°, 270°, including Corridor Format | |
| Pan/Tilt/Zoom | Digital PTZ | |
| Audio | | |
| Audio input/output | Audio features through portcast technology: two-way audio connectivity, voice enhancer | |
| Network | | |
| Network protocols | IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS, TLS, QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP®, SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SRTP/RTSPS, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCP, ARP, SSH, HDMI, LLDP, CDP, MQTT v3.1.1, Link-Local address (ZeroConf) | |
| System integration | | |
| Application Programming Interface | Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at axis.com One-click cloud connection ONVIF® Profile G, ONVIF® Profile M, ONVIF® Profile S, and ONVIF® Profile T, specification at onvif.org Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX. | |
| Video management systems | Compatible with AXIS Camera Station Edge, AXIS Camera Station Pro, AXIS Camera Station 5, and video management software from Axis' partners available at axis.com/vms . | |
| Event conditions | Device status: above operating temperature, above or below operating temperature, below operating temperature, IP address | |
| Event actions | MQTT publish Notification: email, HTTP, HTTPS, TCP and SNMP trap Overlay text, zoom preset, day/night mode Pre- and post-alarm video or image buffering for recording or upload Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email External output activation via AXIS T61 Audio and I/O Interfaces with portcast technology | |
| Built-in installation aids | Remote zoom, remote focus | |
| Analytics | | |
| Applications | Included AXIS Live Privacy Shield ^b , AXIS Object Analytics, AXIS Scene Metadata, AXIS Video Motion Detection, AXIS Face Detector Supported AXIS People Counter AXIS Queue Monitor Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap | |
| AXIS Object Analytics | Object classes: humans, vehicles (types: cars, buses, trucks, bikes) Scenarios: line crossing, object in area, crossline counting, occupancy in area, time in area Up to 10 scenarios Other features: triggered objects visualized with color-coded bounding boxes Polygon include/exclude areas Perspective configuration ONVIF Motion Alarm event | |
| AXIS Scene Metadata | Object classes: humans, faces, vehicles (types: cars, buses, trucks, bikes), license plates Object attributes: vehicle color, upper/lower clothing color, confidence, position | |
| Approvals | | |
| EMC | EN 55032 Class A, EN 55035, EN 61000-6-1, EN 61000-6-2 Australia/New Zealand: CISPR 24, CISPR 35, RCM AS/NZS CISPR 32 Class A Canada: ICES-3(A)/NMB-3(A) Japan: VCCI Class A Korea: KC KN32 Class A, KC KN35 USA: FCC Part 15 Subpart B Class A | |
| Safety | IEC/EN/UL 62368-1, CAN/CSA C22.2 No. 62368-1, IS 13252 IEC 62471 | |
| Environment | IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-6, IEC/EN 60529 IP42, IEC/EN 62262 IK08 | |
| Network | NIST SP500-267 | |
| Cybersecurity | ETSI EN 303 645 | |
| Cybersecurity | | |
| Edge security | Software: Signed OS, brute force delay protection, digest authentication and OAuth 2.0 RFC6749 OpenID Authorization Code Flow for centralized ADFS account management, password protection, AES-XTS-Plain64 256bit SD card encryption Hardware: Axis Edge Vault cybersecurity platform Secure element (CC EAL 6+), system-on-chip security (TEE), Axis device ID, secure keystore, signed video, secure boot, encrypted filesystem (AES-XTS-Plain64 256bit) | |
| Network security | IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2), IEEE 802.1AE (MACsec PSK/EAP-TLS), IEEE 802.1AR, HTTPS/HSTS, TLS v1.2/v1.3, Network Time Security (NTS), X.509 Certificate PKI, host-based firewall | |

| | |
|------------------------|--|
| Documentation | <p><i>AXIS OS Hardening Guide</i> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> AXIS OS Software Bill of Material (SBOM)</p> <p>To download documents, go to axis.com/support/cybersecurity/resources To read more about Axis cybersecurity support, go to axis.com/cybersecurity</p> |
| General | |
| Casing | <p>IP42 water- and dust-resistant, IK08 impact-resistant, polycarbonate and aluminum casing with hard-coated dome Encapsulated electronics Color: white NCS S 1002-B For repainting instructions of casing and impact on warranty, contact your Axis partner.</p> |
| Sustainability | PVC free, BFR/CFR free, 43% recycled plastics |
| Power | Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Typical 5 W, max 9.7 W |
| Connectors | <p>RJ45 10BASE-T/100BASE-TX PoE HDMI type D Audio: Audio and I/O connectivity via portcast technology</p> |
| IR illumination | <p>OptimizedIR with power-efficient, long-life 855 nm IR LEDs Range of reach 20 m (65.6 ft) or more depending on the scene</p> |
| Storage | <p>Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com</p> |

| | |
|-----------------------------|---|
| Operating conditions | <p>0 °C to 45 °C (32 °F to 113 °F) Humidity 10–85% RH (non-condensing)</p> |
| Storage conditions | <p>-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)</p> |
| Dimensions | <p>Height: 71 mm (2.8 in) ø 121 mm (4.76 in)</p> |
| Weight | 375 g (0.83 lb) |
| Included accessories | Installation guide, Windows® decoder 1-user license |
| Optional accessories | <p>AXIS TM3207 Recessed Mount AXIS T94C01L Recessed Mount AXIS T94C01U Universal Mount AXIS T94C01M J-Box/Gang Box Plate AXIS M42 Casing A Black 4P AXIS M42 Smoked Dome A 4P AXIS T91A33 Lighting Track Mount AXIS T91A23 Tile Grid Ceiling Mount AXIS TM3101 Pendant Wall Mount AXIS Surveillance Cards For more accessories, see axis.com</p> |
| Languages | English, German, French, Spanish, Italian, Russian, Japanese, Korean, Portuguese, Simplified Chinese, Traditional Chinese, Dutch, Czech, Swedish, Finnish, Turkish, Thai, Vietnamese |
| Warranty | 5-year warranty, see axis.com/warranty |

- a. *Reduced frame rate in Motion JPEG*
 b. *16:9 capture mode required*

Highlighted capabilities

AXIS Object Analytics

AXIS Object Analytics is a preinstalled, multifeatured video analytics that detects and classifies humans, vehicles, and types of vehicles. Thanks to AI-based algorithms and behavioral conditions, it analyzes the scene and their spatial behavior within – all tailored to your specific needs. Scalable and edge-based, it requires minimum effort to set up and supports various scenarios running simultaneously.

Axis Edge Vault

Axis Edge Vault is the hardware-based cybersecurity platform that safeguards the Axis device. It forms the foundation that all secure operations depend on and offer features to protect the device's identity, safeguard its integrity and protect sensitive information from unauthorized access. For instance, **secure boot** ensures that a device can boot only with **signed OS**, which prevents physical supply chain tampering. With signed OS, the device is also able to validate new device software before accepting to install it. And the **secure keystore** is the critical building-block for protecting cryptographic information used for secure communication (IEEE 802.1X, HTTPS, Axis device ID, access control keys etc.) against malicious extraction in the event of a security breach. The secure keystore and secure connections are provided through a Common Criteria or FIPS 140 certified hardware-based cryptographic computing module.

Furthermore, signed video ensures that video evidence can be verified as untampered. Each camera uses its unique video signing key, which is securely stored in the secure keystore, to add a signature into the video stream allowing video to be traced back to the Axis camera from where it originated.

To read more about Axis Edge Vault, go to axis.com/solutions/edge-vault.

Lightfinder

The Axis Lightfinder technology delivers high-resolution, full-color video with a minimum of motion blur even in near darkness. Because it strips away noise, Lightfinder makes dark areas in a scene visible and captures details in very low light. Cameras with Lightfinder discern color in low light better than the human eye. In surveillance, color may be the critical factor to identify a person, an object, or a vehicle.

OptimizedIR

Axis OptimizedIR provides a unique and powerful combination of camera intelligence and sophisticated LED technology, resulting in our most advanced camera-integrated IR solutions for complete darkness. In our pan-tilt-zoom (PTZ) cameras with OptimizedIR, the IR beam automatically adapts and becomes wider or narrower as the camera zooms in and out to make sure that the entire field of view is always evenly illuminated.

Zipstream

The Axis Zipstream technology preserves all the important forensic in the video stream while lowering bandwidth and storage requirements by an average of 50%. Zipstream also includes three intelligent algorithms, which ensure that relevant forensic information is identified, recorded, and sent in full resolution and frame rate.

For more information, see axis.com/glossary