

# AXIS W800 System Controller

For flexible, scalable solutions

AXIS W800 System Controller is the central integration and management point of the body worn solution. The modular design of the system controller ensures a flexible and highly scalable system. A single AXIS W800 supports up to five docking stations and 40 cameras but can easily be extended with additional system controllers for larger body worn systems.

- > **High speed supervised offloading**
- > **Flexible and scalable**
- > **Single system integration point**
- > **Centralized system management**



# AXIS W800 System Controller

<b>Network</b>		<i>Axis Security Development Model</i> AXIS OS Software Bill of Material (SBOM) To download documents, go to <a href="https://axis.com/support/cybersecurity/resources">axis.com/support/cybersecurity/resources</a> To read more about Axis cybersecurity support, go to <a href="https://axis.com/cybersecurity">axis.com/cybersecurity</a>
<b>Security</b>	HTTPS <sup>a</sup> encryption, IEEE 802.1x (EAP-TLS) <sup>a</sup> network access control	
<b>Network protocols</b>	IPv4, IPv6 USGv6, HTTPS <sup>a</sup> , TLS <sup>a</sup> , Bonjour, DNS, NTP, NTS, SRTP/RTSPS, TCP, UDP, ICMP, DHCP, ARP	
<b>Throughput</b>	Camera to system controller: 100 Mbit/s (per camera) System controller to content destination: 1 Gbit/s	
<b>System integration</b>		
<b>Application Programming Interface</b>	Body Worn Integration API	
<b>Content destinations</b>	<b>Evidence management systems</b> Third party evidence management software from Axis Application Development Partners <b>Video management systems</b> AXIS Camera Station, and other third party video management software from Axis Application Development Partners available at <a href="https://axis.com/vms">axis.com/vms</a>	
<b>Approvals</b>		
<b>EMC</b>	EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2 Australia/New Zealand: RCM AS/NZS CISPR 32 Class A Canada: ICES-3(A)/NMB-3(A) Japan: VCCI Class A Korea: KC KN32 Class A, KC KN35 USA: FCC Part 15 Subpart B Class A	
<b>Safety</b>	IEC/EN/UL 62368-1, IS 13252	
<b>Environment</b>	IEC 60068-2-1, IEC 60068-2-14, IEC 60068-2-2, IEC 60068-2-27, IEC 60068-2-6, IEC 60068-2-78, IEC/EN 60529 IP3X	
<b>Network</b>	NIST SP500-267	
<b>Cybersecurity</b>	ETSI EN 303 645, FIPS 140	
<b>Cybersecurity</b>		
<b>Edge security</b>	<b>Software:</b> Signed OS, brute force delay protection, digest authentication and OAuth 2.0 RFC6749 OpenID Authorization Code Flow for centralized ADFS account management, password protection, AES-XTS-Plain64 256bit SD card encryption <b>Hardware:</b> Axis Edge Vault cybersecurity platform TPM 2.0 (CC EAL4+, FIPS 140-2 Level 2), system-on-chip security (TEE), secure keystore, secure boot, encrypted filesystem (AES-XTS-Plain 256bit)	
<b>Network security</b>	IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2) <sup>a</sup> , IEEE 802.1AR, HTTPS/HSTS <sup>a</sup> , TLS v1.2/v1.3 <sup>a</sup> , Network Time Security (NTS), X.509 Certificate PKI, host-based firewall	
<b>Documentation</b>	AXIS OS Hardening Guide Axis Vulnerability Management Policy	
<b>General</b>		
<b>Casing</b>	IP3X-rated Aluminum and plastic casing Color: black NCS S 9000-N	
<b>Mounting</b>	Mounting bracket	
<b>Sustainability</b>	PVC free	
<b>Power</b>	12 V DC, Typical 12.25 W, max 16 W	
<b>Connectors</b>	1 x (uplink) Shielded RJ45 10BASE-T/100BASE-TX/1000BASE-T 5 x (device network) Shielded RJ45 10BASE-T/100BASE-TX/1000BASE-T USB 2.0 DC connector for 12 V DC input	
<b>Storage</b>	480 GB SSD	
<b>Operating conditions</b>	0 °C to 40 °C (32 °F to 104 °F) Humidity 10–85% RH (non-condensing)	
<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)	
<b>Dimensions</b>	<b>AXIS W800 System Controller</b> Height: 53 mm (2.1 in) Width: 180 mm (7.1 in) Length: 180 mm (7.1 in) <b>Mounting bracket</b> Height: 57 mm (2.2 in) Width: 185 mm (7.3 in) Length: 198 mm (7.8 in)	
<b>Weight</b>	<b>AXIS W800 System Controller</b> 765 g (1.7 lb) <b>Mounting bracket</b> 408 g (0.90 lb)	
<b>Included accessories</b>	Mounting bracket	
<b>Optional accessories</b>	AXIS TW8100 Rack Mount External Secured RFID Card Reader 125kHz + 13.56MHz with NFC (USB)	
<b>Languages</b>	English, German, French, Spanish, Italian	
<b>Warranty</b>	5-year warranty, see <a href="https://axis.com/warranty">axis.com/warranty</a>	

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).