

AXIS P3255-LVE Dome Camera

Streamlined fixed dome for analytics with deep learning

This outdoor-ready, vandal-resistant fixed dome features a deep-learning processing unit that provides the perfect platform for developing customized analytics based on deep learning. By running analytics directly on the camera (on the edge), there's no need for expensive servers resulting in a faster and more scalable system. AXIS P3255-LVE offers excellent video quality in HDTV 1080p and includes OptimizedIR illumination and Forensic WDR for sharp video even in challenging light or complete darkness. It features AXIS Object Analytics for nuanced and remarkably granular object classification. Furthermore, it's packed with enhanced security functionality to prevent unauthorized access and safeguard your system.

- > [Powerful AI with deep learning](#)
- > [Granular object classification](#)
- > [Support for 3rd-party AI applications](#)
- > [Edge-based processing for scalability](#)
- > [Lightfinder 2.0, Forensic WDR, OptimizedIR](#)



AXIS P3255-LVE Dome Camera

Camera	
Image sensor	1/2.8" progressive scan RGB CMOS
Lens	Varifocal, 3.4–8.9 mm, F1.8 Horizontal field of view: 100°–36° Vertical field of view: 53°–20° Remote zoom and focus, P-Iris control, IR corrected
Day and night	Automatically removable infrared-cut filter
Minimum illumination	With Forensic WDR and Lightfinder 2.0: Color: 0.1 lux at 50 IRE, F1.8 B/W: 0.02 lux at 50 IRE, F1.8; 0 lux with IR illumination on
Shutter speed	1/66500 s to 2 s
Camera adjustment	Pan ±180°, tilt ±75°, rotation ±175°
System on chip (SoC)	
Model	ARTPEC-7
Memory	2048 MB RAM, 1024 MB Flash
Compute capabilities	Deep learning processing unit (DLPU)
Video	
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG
Resolution	1920x1080 to 160x90
Frame rate	With WDR: 25/30 fps with power line frequency 50/60 Hz Without WDR: 50/60 fps with power line frequency 50/60 Hz
Video streaming	Multiple, individually configurable streams in H.264, H.265, and Motion JPEG Axis Zipstream technology for H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 Low latency mode
Multi-view streaming	Up to 2 individually cropped out view areas in full frame rate streaming
Image settings	Compression, color saturation, brightness, sharpness, contrast, local contrast, white balance, day/night threshold, tone mapping, exposure control (including automatic gain control), exposure zones, defogging, Forensic WDR: up to 120 dB depending on scene, barrel distortion correction, fine tuning of low-light behavior, dynamic text and image overlay, privacy masks, mirroring, rotation: 0°, 90°, 180°, 270°, including Corridor Format
Pan/Tilt/Zoom	Digital PTZ, preset positions
Audio	
Audio streaming	Full duplex
Audio encoding	24bit LPCM, AAC-LC 8/16/32/44.1/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz Configurable bit rate
Audio input/output	External microphone input, line input, digital input with ring power, line output, automatic gain control Two-way audio connectivity via AXIS T61 Audio and I/O Interfaces with portcast technology (no support for AXIS T61 Mk II)
Network	
Security	IP address filtering, HTTPS ^a encryption, IEEE 802.1X (EAP-TLS) ^b network access control, user access log, centralized certificate management, signed video, Axis Edge Vault, Axis device ID
Network protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS ^c , HTTP/2, TLS ^d , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP ^e , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SRTP/RTSPS, TCP, UDP, IGMP, RTCP, ICMP, DHCPv4/v6, ARP, SSH, SIP, LLDP, CDP, MQTT, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf)
System integration	
Application Programming Interface	Open API for software integration, including VAPIX [®] , metadata, and AXIS Camera Application Platform (ACAP); specifications at axis.com/developer-community . One-click cloud connection
	ONVIF [®] Profile G, ONVIF [®] Profile M, ONVIF [®] Profile S, and ONVIF [®] Profile T, specification at onvif.org Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX
Video management systems	Compatible with AXIS Camera Station Edge, AXIS Camera Station Pro, AXIS Camera Station 5, and video management software from Axis' partners available at axis.com/vms .
Event conditions	Analytics, external input, supervision of input, edge storage events, virtual inputs through API MQTT subscribe
Event actions	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share, and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP, and SNMP trap MQTT publish Overlay text, external output activation, play audio clip, make call
Built-in installation aids	Pixel counter, remote focus, remote zoom OptimizedIR with adjustable IR illumination intensity
Analytics	
Applications	Included AXIS Live Privacy Shield, AXIS Object Analytics, AXIS Scene Metadata, AXIS Video Motion Detection, active tampering alarm, audio detection Supported AXIS Perimeter Defender, AXIS License Plate Verifier Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap .
AXIS Object Analytics	Object classes: humans, vehicles (types: cars, buses, trucks, bikes, other) Scenarios: line crossing, object in area, crossline counting, time in area Up to 10 scenarios Other features: visualized with trajectories, color-coded bounding boxes and tables Polygon include/exclude areas Perspective configuration ONVIF Motion Alarm event
AXIS Scene Metadata	Object classes: Classes: humans, faces, vehicles (types: cars, buses, trucks, bikes), license plates Confidence, position
Approvals	
EMC	EN 55032 Class A, EN 50121-4, EN 55024, EN 61000-6-1, EN 61000-6-2 Australia/New Zealand: RCM AS/NZS CISPR 32 Class A Canada: ICES-3(A)/NMB-3(A) Japan: VCCI Class A Korea: KC KN32 Class A, KC KN35 USA: FCC Part 15 Subpart B Class A Railway: IEC 62236-4
Safety	IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, IS 13252, IEC/EN 62471
Environment	IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP66, IEC/EN 62262 IK10, NEMA 250 Type 4X, NEMA TS 2 (2.2.7-2.2.9)
Network	NIST SP500-267
Cybersecurity	ETSI EN 303 645, BSI IT Security Label
Cybersecurity	
Edge security	Software: Signed OS, brute force delay protection, digest authentication and OAuth 2.0 RFC6749 OpenID Authorization Code Flow for centralized ADFS account management, password protection, AES-XTS-Plain64 256bit SD card encryption Hardware: Axis Edge Vault cybersecurity platform Secure element (CC EAL 6+), secure keystore, secure boot
Network security	IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2) ^e , IEEE 802.1AE (MACsec PSK/EAP-TLS), IEEE 802.1AR, HTTPS/HSTS ^f , TLS v1.2/v1.3 ^g , Network Time Security (NTS), X.509 Certificate PKI, host-based firewall

Documentation	<p><i>AXIS OS Hardening Guide</i> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> AXIS OS Software Bill of Material (SBOM)</p> <p>To download documents, go to axis.com/support/cybersecurity/resources To read more about Axis cybersecurity support, go to axis.com/cybersecurity</p>
General	
Casing	<p>IP66- and NEMA 4X-rated, IK10 impact-resistant polycarbonate casing with hard-coated dome and dehumidifying membrane Encapsulated electronics and captive screws Color: white NCS S 1002-B For repainting instructions and impact on warranty, contact your Axis partner.</p>
Mounting	<p>Mounting bracket with holes for junction box (double-gang, single-gang, and 4" octagon) and for wall or ceiling mount ¼"-20 UNC tripod screw thread</p>
Sustainability	PVC free
Power	<p>Power over Ethernet (PoE) IEEE 802.3at Type 2 Class 4 Typical 7.8 W, max 14.6 W</p>
Connectors	<p>RJ45 10BASE-T/100BASE-TX PoE I/O: 4-pin 2.5 mm (0.098 in) terminal block for 1 supervised digital input and 1 digital output (12 V DC output, max. load 25 mA) Audio: 4-pin 2.5 mm (0.098 in) terminal block for audio in and out Audio and I/O connectivity via AXIS T61 Audio and I/O Interfaces with portcast technology (no support for AXIS T61 Mk II)</p>
IR illumination	<p>Optimized IR with power-efficient, long-life 850 nm IR LEDs Range of reach 40 m (130 ft) or more depending on the scene</p>
Storage	<p>Support for microSD/microSDHC/microSDXC card and encryption Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com</p>
Operating conditions	<p>-40 °C to 50 °C (-40 °F to 122 °F) Maximum temperature (intermittent): 55 °C (131 °F) Maximum temperature according to NEMA TS 2 (2.2.7): 74 °C (165 °F) Start-up temperature: -30 °C to 50 °C (-22 °F to 122 °F)</p>

	Humidity 10–100% RH (condensing)
Storage conditions	<p>-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)</p>
Dimensions	<p>Without weathershield: Height: 104 mm (4.09 in) ø 149 mm (5.87 in)</p>
Weight	<p>With weathershield: 800 g (1.8 lb)</p>
Included accessories	<p>Installation guide, Windows® decoder 1-user license, drill template, Resistorx® T20 L-key, terminal block connectors, cable gaskets, connector guard, weathershield</p>
Optional accessories	<p>AXIS T94M02L Recessed Mount, AXIS T94T01D Pendant Kit, AXIS Dome Intrusion Switch C, AXIS T6101 Audio and I/O Interface, AXIS T6112 Audio and I/O Interface, AXIS ACI Conduit Adapters, Axis mounts and microphones, smoked dome, black casing For more accessories, see axis.com</p>
Languages	<p>English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese, Dutch, Czech, Swedish, Finnish, Turkish, Thai, Vietnamese</p>
Warranty	5-year warranty, see axis.com/warranty

- This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*
- This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*
- This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*
- This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*
- This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*
- This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*
- This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*