

AXIS Camera Station S2212 Appliance

All-in-one recorder with PoE switch for UHD surveillance

AXIS Camera Station S2212 Appliance is an all-in-one recording solution with integrated, manageable PoE switch designed to deliver reliable high-definition surveillance with up to 4K resolution. For quick and easy installation, AXIS S2212 is preconfigured and preloaded with AXIS Camera Station video management software, and includes licenses for 12 channels plus all necessary system software. AXIS Camera Station offers an intuitive user interface that allows users to take full advantage of Axis wide range of video surveillance cameras and other IP products. With the operating system stored on a solid-state drive (SSD) and 5-year warranty, AXIS S2212 provides a reliable surveillance solution.

- > [All-in-one solution with integrated PoE switch](#)
- > [High-definition surveillance with up to 4K resolution](#)
- > [AXIS Camera Station licenses included](#)
- > [Full compatibility with Axis products](#)



AXIS Camera Station S2212 Appliance

Licenses	12 AXIS Camera Station core licenses included and tied to the hardware. Can be upgraded with additional licenses (sold separately).	Supports only one monitor Playback at high speeds can affect video performance.
System scalability	Qualified for up to 12 video channels and 24 doors	Recording Qualified for recording up to 12 video channels with a total recording rate up to 192 Mbit per second
Hardware		
Processor	Intel® Core™ i3	General
Memory	8 GB	Operating system Microsoft® Windows® 10 IoT Enterprise Operating system recovery: yes Operating system drive: 120 GB SSD
Storage	Surveillance Class HDD Total HDD slot: 2 Free HDD slot: 1 Out-of-the-box storage: 6 TB (1x6 TB)	Security Security support for encrypted operating system drive and recording drive FIPS 140-2 level 2 certified Trusted Platform Module (TPM 2.0)
Switch	12 ports integrated, 135 W total power budget Power over Ethernet (PoE) IEEE 802.3at Class 4	Operating conditions 0 °C to 40 °C (32 °F to 104 °F) Humidity: 10–90% RH (non-condensing)
Graphics card	Intel® HD Graphics	Storage conditions -40 °C to 65 °C (-40 °F to 149 °F) Humidity: 10–90% RH (non-condensing)
Power	Max 270 W, 135 W PoE dedicated 100 – 240 V AC, 3.5 A, 50/60 Hz 54 V DC, 5 A External power adapter	Approvals EMC CNS 13438, EAC, EN 55024, EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A Safety IEC/EN 60950-1, IEC/EN 62368-1, KC-Mark, UL 62368-1, IS 13252
Connectors	Front side: 1x USB 3.0 1x Audio line in 1x Audio line out Rear side Switch: 12x PoE ports 10/100 Mbps 1x SFP 10/100/1000 Mbps 1x RJ45 10/100/1000 Mbps Rear side Server: 1x RJ45 10/100/1000 Mbps 2x USB 2.0 1 Displayport™ 1 HDMI port	Dimensions 330 x 230 x 78 mm (13 x 9.1 x 3.1 in) Weight 5.8 kg (12.8 lb) Included accessories Rack ears, power adapter Optional accessories Surveillance Hard Drive 6 TB available from Axis AXIS TS2901 Appliance Stand Axis desktop terminals Axis Ethernet surge protector For more accessories, see axis.com
Video		
Video streaming	Live view: 1 x 4K stream full screen 4 split x 1080p Up to 12 cameras split view Supports two monitors, maximum one 4K monitor recommended Playback: Supports the same split scenarios as live view	Warranty Recorder and hard drive: 5-year warranty, see axis.com/warranty Export control This product is subject to export control regulations, and you should always comply with all applicable national and international export or re-export control regulations.

AXIS Camera Station

This product does not support the free text search functionality due to limited RAM.
For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on axis.com