

## AXIS Camera Station S1296 Rack Recording Server

Flexible and scalable recording server

Featuring powerful components, this secure, scalable recording server offers high performance and support for powerful applications and features. It includes AXIS Camera Station licenses and multiple RAID configurations for flexible storage and multiple redundancy configuration. And, a Trusted Platform Module (FIPS 140-2 level 2 certified) ensures secure storage of all cryptographic keys and certificates. Available in two variants with a choice of storage, it comes preloaded with preconfigured software. Plus, all supported products are available in one price list for a one-stop-shop experience. Furthermore, it offers services such as Keep Your Hard Drive, Next Business Day Onsite Support, and a 5-year warranty.

- > Scalable and powerful solution
- > Flexible storage options including RAID
- > Available in 2 variants: 96 TB and 192 TB
- > 96 AXIS Camera Station licenses included
- > Extensive support and 5-year warranty



## AXIS Camera Station S1296 Rack Recording Server

Variants	S1296 Rack 96 TB S1296 Rack 192 TB	Safety
Licenses	96 AXIS Camera Station core licenses included and tied to the hardware. Can be upgraded with additional licenses (sold separately).	Cyberse Cybers Docume
System scalability	Qualified for 192 doors and a recording bitrate up to 1.5 Gbit/s, 150 video channels at 4 MP, 30 fps in a retail scenario. Check AXIS Site Designer for storage estimates. Tested with: 20 live view clients 4 clients performing heavy playback or scrubbing operations	Docume
Hardware		Genero
Processor	Intel® Xeon® Silver	Operatio
Memory	2x 16 GB	
Storage	S1296 Rack 96 TB Hot swappable Enterprise Class HDD Total HDD slot: 12	Remote manage
	Free HDD slot: 0 Out-of-the-box storage: 80 TB after RAID 6 Out-of-the-box capacity without RAID: 96 TB (12x8 TB) S1296 Rack 192 TB	Security
	Hot swappable Enterprise Class HDD Total HDD slot: 12	Operation condition
	Free HDD slot: 0 Out-of-the-box storage: 160 TB after RAID 6 Out-of-the-box capacity without RAID: 192 TB (12x16 TB)	Storage conditio
RAID	Factory RAID level: 6 Supported RAID levels: 0, 1, 5, 6, 10	Dimensi
Power	2 x 800 W hot-plug redundant power supplies (included) (100-240 V AC, 12-6.3 A, 50/60 Hz)	
Connectors	Front side: 1x USB 2.0 1x VGA	
	1x iDRAC direct port Rear side:	Weight
	1x USB 2.0	Included
	1x USB 3.0 1x VGA	accesso
	1x iDRAC dedicated Ethernet port	Optiona
	2x RJ45 1 Gbps (Do not use) 2x RJ45 10 Gbps	accesso
Video		Scifices
Video streaming	Not intended for local viewing of video. Recommended to use Axis workstations.	Warran
Approvals		a. Units p. b. Only vo
Supply chain	TAA compliant	c. Units p d. Units p
EMC	EN 55032 Class A, EN 55024, EN 55035, EN 61000-3-2, EN 61000-3-3, FCC Part 2 and 15 Class A, ISED ICES-003 Class A, RCM AS/NZS CISPR 32 Class A, KS C 9832 Class A, KS C 9835, VCCI 32-1 Class A, BSMI	p

Safety	IEC/EN/UL 60950-1, IEC/EN/UL 62368-1, EN 62311, NOM-019-SCFI-1998	
Cybersecurity	FIPS 140	
Cybersecurity		
Documentation	AXIS Camera Station Hardening Guide Axis Vulnerability Management Policy Axis Security Development Model To download documents, go to axis.com/support/cybersecu- rity/resources To read more about Axis cybersecurity support, go to axis.com/cybersecurity	
General		
Operating system	Microsoft® Windows® 10 IoT Enterprise LTSC 2021 Built-in operating system recovery: yes Operating system drive: 480 GB SSD <sup>a</sup>	
Remote server management	iDRAC 9 express license	
Security	Support for encrypted operating system drive and recording drive FIPS 140-2 level 2 certified Trusted Platform Module (TPM 2.0) Secure Component Verification (SCV) <sup>b</sup>	
Operating conditions	10 °C to 35 °C (50 °F to 95 °F) Humidity 20–80% RH (non-condensing)	
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)	
Dimensions	721.62 x 482 x 87 mm (28.42 x 19 x 3.43 in), 2U chassis <b>Rail sizing:</b> Type: sliding Minimum rail mounting depth: 719 mm (28.31 in) Square-hole rack adjustment range: 631-868 mm (24.85-34.18 in) For more information, see the Dell EMC Enterprise Systems Rail Sizing and Rack Compatibility Matrix	
Weight	S1296 Rack 96 TB 26.1kg (57.54 lb) <sup>c</sup> S1296 Rack 192 TB 26.3 kg (57.98 lb) <sup>d</sup>	
Included accessories	Dell Ready Rails 2U Sliding Rails, 2x C13 to C14 power cords for rack PDU (Wall plug power cords are not included)	
Optional accessories	Axis workstations For more accessories, see <i>axis.com</i>	
Services	Next Business Day Onsite Support Keep Your Hard Drive	
Warranty	5-year warranty, see axis.com/warranty	

produced prior to September 1, 2024: 240 GB SSD valid for units produced from September 1, 2024 produced prior to September 1, 2024: 26.1kg (57.54 lb) produced prior to September 1, 2024: 25.6 kg (56.44 lb)

## **AXIS Camera Station**

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on axis.com



