

AXIS Body Worn Live

Right there with you

AXIS Body Worn Live streams live video, audio and metadata from Axis body worn cameras. Let Axis host it for you or host it yourself if cloud-based hosting isn't an option for your organization. It is secure and reliable, it supports informed decision making by operators and provides an added sense of safety for the camera wearers. AXIS Body Worn Live has several layers of security, and the transmission is protected by full end-to-end encryption, ensuring that the customer owns their encryption keys. Being a web-based application it's compatible with PCs, tablets and Android mobile devices and with the self-hosted option it is integrated directly in your preferred VMS.

- > **Hosted by Axis or hosted by you**
- > **Video, audio, and metadata in real-time**
- > **Data retention for instant playback**
- > **End-to-end encryption**
- > **Independent of VMS or EMS**

AXIS Body Worn Live

General	
Variants	Axis-hosted Self-hosted
Supported devices	AXIS W102 Body Worn Camera, AXIS W110 Body Worn Camera, AXIS W120 Body Worn Camera Axis-hosted: AXIS W100 Body Worn Camera, AXIS W101 Body Worn Camera
Configuration	Web browser
Storage	Axis-hosted: 24-hour retention time Metadata storage location: Global Evidence data storage locations: Australia, Canada, EU, France, Germany, India, Japan, Switzerland, United Kingdom, United States (East, West)
Compliance	CJIS-compliant data transfer Axis-hosted: CJIS-compliant storage Data servers supporting regional regulatory requirements for personal integrity
Administration	Centralized user and access management Axis-hosted: Multifactor authentication through My Axis
Data streaming	Video, audio, location
Languages	English Axis-hosted: German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese, Dutch, Czech, Swedish, Finnish, Turkish, Thai, Vietnamese, Romanian, Arabic, Farsi, Hebrew
Cybersecurity	
Security	Axis-hosted: End-to-end encryption: XChaCha20-Poly1305, X25519 and XSalsa20 Encryption at rest: AES-256 bit
	Encryption in transit: TLSv1.2 or later with 256 bit ciphers Self-hosted: Encryption in transit: TLSv1.2 or later, dTLS 1.0 or later, SRTP
Video	
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles 640x360 @ 25/30 fps Bandwidth requirements: up to 8 Mbit/s
Resolution	1280x720 to 640x360
Frame rate	25/30 fps with power line frequency 50/60 Hz
Audio	
Audio encoding	AAC Self-hosted: Opus
Capabilities	
Functionality	Axis-hosted: Live stream triggers: Camera button Stream gap retrieval Priority upload of latest data Pre-buffer Multiple clients can view the same stream Acknowledge stream Self-hosted: Depends on VMS integration
Recording playback	Axis-hosted: Access to recent streams for 24 hours Multiple simultaneous streams Time line scrubbing in live stream Go to live Audio mute Self-hosted: Depends on VMS integration
Positioning system	Axis-hosted: Location data through GNSS