

AXIS Camera Station Edge

Camera-to-cloud video management

This camera-to-cloud VMS makes it easy to manage your video surveillance. A user-friendly interface lets you view live video, search timelines, and export recordings. It's also possible to receive real-time alert notifications from anywhere, anytime. It requires minimum maintenance and includes continuous updates. Licenses come with all Axis devices – simply insert an SD card or use an AXIS S30 Recorder and you're ready to go. It's easy to add new sites and devices to existing sites and there's no need to manually configure each device. Furthermore, with out-of-the-box security and full system encryption as default, it helps you stay secure.

- > Leverages Axis edge devices and the cloud
- > Intuitive live view, timeline search, and video export
- > Quick and secure access anytime, anywhere
- > Easy setup, no server needed
- > Licenses included with Axis devices



AXIS Camera Station Edge

General		Pan/Tilt/Zoom	Control of PTZ and dome cameras using mouse or joystick
Languages	English, Dutch, French, German, Italian, Japanese, Spanish, Swedish	Playback	
Supported devices	Axis network cameras and encoders with firmware 5.50 or later when used together with AXIS S3008 Recorder (solutions not including AXIS S3008 Recorder, are compatible with firmware 8.40 or later), Axis network speakers, Axis network door stations. Functionality based on Axis Cloud Connect requires AXIS OS version 11.11 or later. For a complete list, see axis.com/products/axis-camera-station-edge#compatible-products	Search for recordings	Search for recordings based on camera, date and time Timeline visualization, video scrubbing
Storage	AXIS Surveillance Cards AXIS S30 Recorder Series	Playback speed	Up to 8x or frame by frame
Capacity	Configurable retention recording, duration can be limited per camera to conform to local legal requirements	Recording export	Single images in JPEG or video sequences in ASF or MP4, installation-free standalone player included, digital signature on exported ASF recordings
Clients	Windows client AXIS Camera Station cloud web client Axis mobile apps for Android devices, iPhone and iPad We reserve the right to limit the amount of relay data used by the web client, Windows client, and mobile app.	Events & alarms	
Cloud services	AXIS Camera Station cloud web client Device management, user management	Event triggers	Events triggered by AXIS Object Analytics video motion detection, AXIS Guard Suite, and I/O
Optional cloud services	AXIS Camera Station Cloud Storage	Event actions	Record, push notifications
Video		System requirements	
Video compression	H.264 (MPEG-4 Part 10/AVC), H.265 (MPEG-H Part 2)	Software	Download for free on axis.com/products/axis-camera-station-edge
Resolution	Supports all resolutions	System requirements	Internet access is required during system setup and management. Live and recorded video available offline
Frame rate	Supports all frame rates	System recommendations	Windows client: OS: Windows 10 64-bit or later, CPU: Intel Core i5, RAM: 4 GB, Graphics card: 256 MB onboard video memory, Network: 100 Mbps, Uninterruptible Power Supply (UPS) Web client: Browsers: Chrome™ version 56 and later / Edge™ version 79 and later / Safari® version 11 and later, CPU: Intel Core i5, RAM: 4 GB, Graphics card: 256 MB onboard video memory, Graphics card driver: Always use the latest version, Internet access: 100 Mbps
Audio		Mobile device requirements	Android 8.1 iOS 15
Audio streaming	Two-way audio streaming	Security	Multiple user access levels with password protection, two-factor authentication (2FA), AXIS S30 Recorder Series and SD card encryption, Axis Secure Remote Access
Audio encoding	AAC audio compression, full duplex for Axis network door station calls, half duplex for other Axis devices		
Camera			
Live view	Live view of up to 36 cameras in full screen, panoramic view, Axis Corridor Format, camera sequence, digital PTZ		