

AXIS Camera Station S2208 Appliance

All-in-one recorder with PoE switch for UHD surveillance

AXIS Camera Station S2208 Appliance is an all-in-one recording solution with integrated, manageable PoE switch designed to deliver reliable high-definition surveillance with up to 4K resolution. For quick and easy installation, AXIS S2208 is preconfigured and preloaded with AXIS Camera Station video management software, and includes licenses for 8 channels plus all necessary system software. AXIS Camera Station offers an intuitive user interface that allows users to take full advantage of Axis wide range of video surveillance cameras and other IP products. With the operating system stored on a solid-state drive (SSD) and 5-year warranty, AXIS S2208 provides a reliable surveillance solution.

- > All-in-one solution with integrated PoE switch
- > High-definition surveillance with up to 4K resolution
- > AXIS Camera Station licenses included
- > Full compatibility with Axis products



www.cxis.com T10136416/EN/M17.3/2501

	AXIS Camera Statio	n S2208 A	Appliance
Licenses	8 AXIS Camera Station core licenses included and tied to the hardware. Can be upgraded with additional licenses (sold separately).		Supports only one monitor Playback at high speeds can affect video performance.
System	Qualified for up to 8 video channels and 16 doors	Recording	Qualified for recording up to 8 video channels with a total recording rate up to 128 Mbit per second
scalability		General	
Hardware	1	Operating system	Operating system Microsoft® Windows® 10 IoT Enterprise Operating system recovery: yes Operating system drive: 120 GB SSD
Processor	Intel® Core TM i3		
Memory	8 GB	Carrelle	
Storage	Surveillance Class HDD Total HDD slot: 2 Free HDD slot: 1	Security	Security support for encrypted operating system drive and recording drive FIPS 140-2 level 2 certified Trusted Platform Module (TPM 2.0)
Switch	Out-of-the-box storage: 4 TB (1x4 TB) 8 ports integrated, 135 W total power budget	Operating conditions	0 °C to 40 °C (32 °F to 104 °F) Humidity: 10–90% RH (non-condensing)
	Power over Ethernet (PoE) IEEE 802.3at Class 4	Storage	-40 °C to 65 °C (-40 °F to 149 °F)
Graphics card	Intel® HD Graphics	conditions	Humidity: 10–90% RH (non-condensing)
Power	Max 270 W, 135 W PoE dedicated 100 - 240 V AC, 3.5 A, 50/60 Hz 54 V DC, 5 A External power adapter	Approvals	EMC CNS 13438, EAC, EN 55024, EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A
Connectors	Front side: 1x USB 3.0 1x Audio line in 1x Audio line out Rear side Switch: 8x PoE ports 10/100 Mbps 1x SFP 10/100/1000 Mbps 1x R145 10/100/1000 Mbps Rear side Server: 1x RJ45 10/100/1000 Mbps 2x USB 2.0 1 Displayport TM 1 HDMI port		Safety IEC/EN 60950-1, IEC/EN 62368-1, KC-Mark, UL 62368-1, IS 13252
		Dimensions	330 x 230 x 78 mm (13 x 9.1 x 3.1 in)
		Weight	5.8 kg (12.8 lb)
		Included accessories	Rack ears, power adapter
		Optional accessories	Surveillance Hard Drive 4 TB available from Axis AXIS TS2901 Appliance Stand Axis desktop terminals Axis Ethernet surge protector
Video			For more accessories, see axis.com
Video streaming	Live view: 1 x 4K stream full screen 4 split x 1080p Up to 8 cameras split view Supports two monitors, maximum one 4K monitor recommended Playback: Supports the same split scenarios as live view	Warranty	Recorder and hard drive: 5-year warranty, see axis.com/warranty
		Export control	This product is subject to export control regulations, and you should always comply with all applicable national and international export or re-export control regulations.

AXIS Camera Station

This product does not support the free text search functionality due to limited RAM.

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on axis.com

