

## AXIS Q1647 Network Camera

5 MP video with 1/2" sensor and i-CS lens

With AXIS Q1647 Network Camera it's easier than ever to capture everything. High resolution at full frame rate, i-CS lens, and 1/2" sensor ensures outstanding details and sharp images. Even in challenging or low light, Forensic WDR and Lightfinder ensures details will be discovered. To minimize vibrations, electronic image stabilization (EIS) keeps the image steady. AXIS Q1647 enables proactive surveillance with preinstalled AXIS Motion Guard and AXIS Fence Guard. Orientation aid enables street view and compass rose for quick orientation with multiple monitors, and Zipstream optimizes the video stream to maintain high video quality while saving bandwidth and storage.

- > **5 MP resolution at 25/30 fps**
- > **1/2" sensor**
- > **Forensic WDR and Lightfinder**
- > **Electronic image stabilization (EIS)**
- > **AXIS Motion Guard and AXIS Fence Guard**



# AXIS Q1647 Network Camera

<b>Camera</b>		<b>Video management systems</b>	Compatible with AXIS Camera Station Edge, AXIS Camera Station Pro, AXIS Camera Station 5, and video management software from Axis' partners available at <a href="http://axis.com/vms">axis.com/vms</a> .
<b>Image sensor</b>	1/2" progressive scan RGB CMOS	<b>Event conditions</b>	Analytics, external input, edge storage events, virtual inputs through API Audio: audio detection Device status: above operating temperature, above or below operating temperature, below operating temperature, IP address removed, network lost, new IP address, storage failure, system ready, within operating temperature Edge storage: recording ongoing, storage disruption I/O: digital input, manual trigger, virtual input MQTT subscribe PTZ: PTZ malfunctioning, PTZ movement, PTZ preset position reached, PTZ ready Scheduled and recurring: scheduled event Video: average bitrate degradation, day-night mode, live stream open, tampering
<b>Lens</b>	Varifocal, IR corrected, CS-mount 3.9–10.0 mm, F1.5 5.3 MP (16:9): Horizontal field of view: 110°–44° Vertical field of view: 59°–24° 4 MP (16:9): Horizontal field of view: 95°–38° Vertical field of view: 52°–21° 5 MP (4:3): Horizontal field of view: 92°–37° Vertical field of view: 68°–27° i-CS lens	<b>Event actions</b>	File upload: FTP, SFTP, HTTP, HTTPS, network share and email, send video clip Notification: email, HTTP, HTTPS and TCP Overlay text, Send SNMP Trap Video and audio recording to edge storage Pre- and post-alarm video buffering External output activation, day/night vision mode, play audio clip, status LED, WDR mode, defog mode, PTZ control MQTT publish
<b>Day and night</b>	Automatically removable infrared-cut filter	<b>Data streaming</b>	Event data
<b>Minimum illumination</b>	5 MP 25/30 fps with WDR and Lightfinder: Color: 0.12 lux at 50 IRE, F1.5; B/W: 0.02 lux at 50 IRE, F1.5 4 MP 50/60 fps: Color: 0.24 lux at 50 IRE, F1.5, B/W; 0.04 lux at 50 IRE, F1.5	<b>Built-in installation aids</b>	i-CS: Remote zoom and focus Other lens: Remote back focus Traffic wizard, pixel counter, levelling assistant, autorotation
<b>Shutter speed</b>	1/100000 to 2 s	<b>Analytics</b>	
<b>Pan/Tilt/Zoom</b>	Digital PTZ, uploadable PTZ driver (Pelco D pre-installed)	<b>Applications</b>	<b>Included</b> AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard AXIS Video Motion Detection, active tampering alarm, audio detection <b>Supported</b> AXIS Digital Autotracking Support for additional applications if the device is used with compatible accessories. For more information, contact your Axis partner. Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://axis.com/acap">axis.com/acap</a>
<b>System on chip (SoC)</b>		<b>Approvals</b>	
<b>Model</b>	ARTPEC-6	<b>EMC</b>	EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2 <b>Australia/New Zealand:</b> RCM AS/NZS CISPR 32 Class A <b>Canada:</b> ICES-003 Class A <b>Japan:</b> VCCI Class A <b>Korea:</b> KCC KN32 Class A, KN35 <b>USA:</b> FCC Part 15 Subpart B Class A
<b>Memory</b>	1 GB RAM, 512 MB Flash	<b>Safety</b>	IEC/EN/UL 62368-1, IS 13252
<b>Video</b>		<b>Environment</b>	IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC), Main, Baseline and High Profile Motion JPEG	<b>Network</b>	NIST SP500-267
<b>Resolution</b>	3072x1728 to 320x180	<b>Cybersecurity</b>	
<b>Frame rate</b>	5 MP with WDR: 25/30 fps with power line frequency 50/60 Hz 4 MP without WDR: 50/60 fps with power line frequency 50/60 Hz	<b>Edge security</b>	<b>Software:</b> Signed OS, brute force delay protection, digest authentication and OAuth 2.0 RFC6749 OpenID Authorization Code Flow for centralized ADFS account management, password protection
<b>Video streaming</b>	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/ABR/MBR H.264	<b>Network security</b>	IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2), IEEE 802.1AE (MACsec PSK/EAP-TLS), HTTPS/HSTS, TLS v1.2/v1.3, Network Time Security (NTS), X.509 Certificate PKI, host-based firewall
<b>Image settings</b>	Saturation, contrast, brightness, sharpness, Forensic WDR – 120 dB, white balance, day/night threshold, exposure mode, exposure zones, compression, orientation: auto, 0°, 90°, 180°, 270° including corridor format, mirroring of images, dynamic text overlay, image overlay, privacy masks, defogging, noise reduction, electronic image stabilization, barrel distortion correction, orientation aid, fine tuning of behavior at low light Scene profiles: forensic, vivid, traffic overview, backlit entrance	<b>Documentation</b>	<i>AXIS OS Hardening Guide</i> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> AXIS OS Software Bill of Material (SBOM) To download documents, go to <a href="http://axis.com/support/cybersecurity/resources">axis.com/support/cybersecurity/resources</a>
<b>Audio</b>			
<b>Audio streaming</b>	Two-way, full duplex		
<b>Audio encoding</b>	AAC-LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz Configurable bit rate		
<b>Audio input/output</b>	External balanced/unbalanced microphone or line input, line output, built-in microphone, automatic gain control 24 bit AD/DA-conversion		
<b>Network</b>			
<b>Network protocols</b>	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTP/2, HTTPS, TLS, QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP™, SNMPv1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SFTP, SRTP/RTSPS, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SSH, LLDP, CDP, MQTT v3.1.1, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf).		
<b>System integration</b>			
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at <a href="http://axis.com">axis.com</a> AXIS Video Hosting System (AVHS) with One-Click Connection One-Click Cloud Connection ONVIF® Profile G, ONVIF® Profile M, ONVIF® Profile S, and ONVIF® Profile T, specifications at <a href="http://onvif.org">onvif.org</a>		

To read more about Axis cybersecurity support, go to [axis.com/cybersecurity](https://axis.com/cybersecurity)

General	
<b>Casing</b>	Metal (zinc) Color lid: Silver - RAL 9006 Color chassi: Black - NCS S 9000-N
<b>Sustainability</b>	PVC free
<b>Power</b>	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Typical 5.3 W, max 10.8 W 8–28 V DC, typical 6.4 W, max 11.2 W
<b>Connectors</b>	Shielded RJ45 10BASE-T/100BASE-TX PoE I/O: 6-pin 2.5 mm terminal block for four configurable inputs/outputs (12 V DC output, max load 50 mA) RS485/RS422, 2 pcs, 2 pos, full duplex, terminal block 3.5 mm mic/line in, 3.5 mm line out i-CS connector (compatible with P-Iris and DC-iris)
<b>Storage</b>	Support for microSD/microSDHC/microSDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see <a href="https://axis.com">axis.com</a>
<b>Operating conditions</b>	-20 °C to 60 °C (-4 °F to 140 °F) Humidity 10–85% RH (non-condensing)

<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
<b>Dimensions</b>	82 x 66 x 210 mm (3.23 x 2.60 x 8.25 in)
<b>Weight</b>	950 g (2.1 lb)
<b>Included accessories</b>	Stand, connector kit, resistor <sup>®</sup> T20 tool, installation guide, Windows <sup>®</sup> decoder 1-user license
<b>Optional lenses</b>	Fujinon Varifocal Lens 8–80 mm, DC-iris Lens CS 12–50 mm F1.4 P-Iris 8 MP Lens i-CS 9–50 mm F1.5 8 MP
<b>Optional accessories</b>	AXIS T90B Illuminators, AXIS T92G Housings, AXIS T93F Housings, Axis network cable couplers, AXIS T8129 PoE Extender, AXIS T8415 Wireless Installation Tool, Axis midspans For more accessories, see <a href="https://axis.com">axis.com</a>
<b>Languages</b>	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese, Dutch, Czech, Swedish, Finnish, Turkish, Thai, Vietnamese
<b>Warranty</b>	5-year warranty, see <a href="https://axis.com/warranty">axis.com/warranty</a>